

Aluminum Flooring Trims / Bars.

BPIR Declaration

Version: V1.11223

Designated building product: Class 1

Declaration

Aluminium Extrusion Co has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Aluminum Flooring Trims / Bars.
Identifier	Alum Bars
Profiles	Commercial - Pinned and Pinnless Floating Floor Trims size (mm) - 5.5, 6.5 ,8,10,12.5,15 Hybrid Stair Nosing and Transition 346 -Naplock Pinned Reeded/Fluted 364 - Carpet to Carpet 365 - Carpet to Vinyl 681- Naplock Pinned Hammered 696 - Naplock Pinless Hammered 851 - Carpet Cove Cap 1491 - Vinyl Cove Cap 1710 - Economy Stair Nosing 2903 - Carpet to Tile 3107 - Aluminium Corner Trim 3754 - Carpet Reducer 3775 - Carpet to Vinyl Bead 4546- Carpet Edge 4547 - Finishing Trim 4548 - Ramp Edge 5960 - Carpet to Carpet Wide (45mm) 6230 - Carpet to Luxury Vinyl Tiles (LVTs)

Description

Gilt Edge Aluminum Flooring Trims / Bars are used to finish off a carpet, tiles, vinyl and LVT edge across a doorway or in other places where it joined against another flooring surface. Designed to provide a professional finished edge.

Material: Aluminium

Colours:

- Black (selected profile).
- Bronze (selected profile).
- Champagne.
- Pewter.
- Silver.

Lengths: 2.44mtr. 2.5mtr. 3.3mtr.

Scope of use

- Suitable for commercial or residential use, mainly indoor.
- Suitable for use on wood or concrete subfloor.

Conditions of use

- All surfaces to be bonded shall be dry, smooth, sound and clean.
- Subfloors must also be free of wax, grease and hydrostatic pressure.
- Measure the area Cut the profile to the sizes required and mitre cut internal and external corners with either a mitre block and hack saw, or radial arm drop saw fitted with a suitable blade.
- Secure trim with correct adhesive or nail for trim style and substrate.

Contributions to compliance

Building Regulations 1992 - Clause B2.3.1-Durability Gilt Edge Aluminum Flooring Trims / Bars, with only normal maintenance, will continue to satisfy the performance requirements of Building Regulations for 5 years.

Supporting documentation

The following additional documentation supports the above statements:

Gilt Edge Floor Trim Brochure	Version February 2022	https://giltedge.co.nz/download/stair-no-sing-transition-brochure?wpdmdl=10853&refresh=622fd314192611647301396
--------------------------------------	-----------------------------	---

For further information supporting Aluminum Flooring Trims / Bars. claims refer to our website.

Contact details.

Manufacture location	New Zealand
Legal and trading name of manufacturer	Aluminium Extrusion Co
Manufacturer address for service	14 Southampton Road Miramar 6022
Manufacturer website	www.alexco.co.nz
Manufacturer email	Anthony.Gibbs@alexco.co.nz
Manufacturer phone number	04 388 1091
Manufacturer NZBN	9429040913544

BPIR Ready selections

Category: Other (custom)