



ARDEX Building Product Information Sheet: Flooring Adhesives

Product name:	ARDEX Flooring adhesives
Product line (the product line from which the product is customised)	Resilient flooring adhesives
Product description and its intended use (measurements, materials, usage)	<p>ARDEX Adhesives designed to bond down resilient floor coverings in accordance with AS 1884:2021.</p> <p>Products Covered by this BPIS:</p> <p>ARDEX AF 143 ARDEX AF 145 ARDEX AF 175 ARDEX AF 325 ARDEX AF 2365 ARDEX AF 2525 ARDEX AF 180 ARDEX AF 455 MS Ardex AF 480 MS ARDEX AF 2270</p>
Product identifier (if applicable):	<p><i>Use product database file SAP code and description (update with BPIS name)</i></p> <p>10518 AF 143 15L 38361 ARDEX AF 145* VINYL PS, 12 kg **NEW** 38359 ARDEX AF 175* LVT, 12kg **NEW** 32328 ARDEX AF 325* 14 kg 38363 ARDEX AF 2365* UNIVERSAL, 14 kg **NEW** 25018 ARDEX AF 2525* 2K HEAVY DUTY, 6 kg 30096 ARDEX AF 180 MS 38030 ARDEX AF 455 MS 22389 ARDEX AF 480 MS 30098 ARDEX AF 2270, 18kg</p>
Place of manufacture:	Overseas
Legal and trading name of the manufacturer(s):	WAKOL GMBH (An ARDEX Group Company)
Legal and trading name of the importer	ARDEX New Zealand Ltd
Address for service:	15 Alfred Street, Onehunga Auckland New Zealand 1061
Website:	ardex.co.nz
Email address	info@ardexnz.com
Phone No	0800 227 339



NZBN	9429037589653
Relevant Building Code clauses:	Clause B2 DURABILITY: Clause B2 DURABILITY: Performance B2.3.1 (a), 5 years. Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1.
Statement on how the building product is expected to contribute to compliance:	<p>ARDEX Flooring adhesives are used under resilient flooring products to provide a suitable bond of the floor covering being installed. ARDEX Flooring Adhesives will assist the Floor Covering meeting the requirements of:</p> <p>Clause B2 DURABILITY: Clause B2 DURABILITY: Performance B2.3.1 (a), 5 years.</p> <p>Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1.</p> <p>Performance testing undertaken by ARDEX include bond strength, set times, length change, compatibility with floor covering etc. These parameters are all set internally for ARDEX to issue appropriate warranties. ARDEX Flooring adhesives are designed to exceed the life expectation of the top floor covering.</p> <p>All ARDEX Flooring adhesives are tested for VOC content.</p>
Limitations on the use of the building product:	Adhesives must be installed in accordance with the relevant data sheet and in accordance with AS 1884:202. Test criteria on substructure must be carried out in accordance with AS 1884: 2021- Including moisture testing and ph testing where required.
Design requirements that would support the use of the building product:	Any application of resilient flooring - tiles, planks, and sheet.
Installation requirements:	All work to be completed in accordance with the technical datasheet, AS 1884:2021 AS/NZS 2455 (where applicable)and Best trade practice. https://www.ardex.co.nz/products_category/flooring/flooring-adhesives/
Maintenance requirements:	No maintenance of the product is required. The floor covering must be maintained in accordance with the manufacturers instructions.
Is the building product/building product line subject to	No



warning or ban under section 26?:	
	ARDEX BPIS Flooring adhesives v1 09.06.23