Giltgrip 22 Carpet Adhesive

BPIR Declaration

Version: 1

Designated building product: Class 1

Declaration

importer Gilt Edge Industries has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name Giltgrip 22 Carpet Adhesive

Line Polymer emulsion based adhesive

Identifier GG22

Description

Giltgrip 22 is a water-based Latex adhesive with low in VOC and has been specifically formulated to provide extra open time for positioning of long runs of commercial carpet before it develops its "leggy" grab and holding power for jute & action backed tufted carpets, woven wilton & axminster carpets and most needle-punched carpets.

Scope of use

For bonding tufted secondary backed carpets (jute, soft and action backed), woven wilton & axminster carpets, most needle-punched carpets as well as cushioned Double Bond underlays to sound, smooth dry subfloors of concrete; conventional sand/cement screeds or underlayment; plywood; hardboard or cement sheet underlays.

Conditions of use

All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive application is 100C. It is recommended that all absorbent substrates be primed with a suitable Acrylic Primer prior to the application of adhesive. Apply using a "V" notched trowel spreader, 1.6mm x 1.6mm x 1.6mm giving a spread rate up to 5m2/litre to adhere the double bond underlay to the entire subfloor area. Use a 2.4mm x 2.4mm x 2.4mm "V" notched trowel

giving a spread rate up to 3m2/litre to adhere smooth back carpet to subfloors or double bond underlay or 3.2mm x 1.6mm x 3.2mm "V" notched trowel giving a spread rate up to 2m2/litre for coarse back, woven or action back carpets to subfloors or double bond underlay. Check to ensure that complete transfer of adhesive to the carpet/underlay has occurred. Roll finished installation with a 25-35Kg roller. Complete the installation according to the adhesive manufacturer's instruction. Do not allow heavy traffic for 24 hours. All Seams should be seamed sealed using a suitable seam sealer. It is strongly recommended that Dual bond seaming tape be used on all seams in double bond installations.

Relevant building code clauses

Contributions to compliance

Building Regulations 1992 - Clause 2B-Durability GiltGrip 22, with only normal maintenance, will continue to satisfy the performance requirements of Building Regulations for 15 years.

Supporting documentation

The following additional documentation supports the above statements:

GiltGrip 22 1- https://giltedge.co.nz/download/tds-gg22-giltgrip-

Technical Data 202322?wpdmdl=8577&refresh=6525ec6833d411696984168

Sheet

GiltGrip 22 1- https://giltedge.co.nz/download/msds-gg22-giltgrip-

Safety Data 202322?wpdmdl=8578&refresh=6525ec684bacf1696984168

Sheet

GiltGrip 22 VOC1- https://giltedge.co.nz/download/voc-gg22-giltgrip-

Report (Test 202322?wpdmdl=8579&refresh=6525ec6862e701696984168

results)

For further information supporting Giltgrip 22 Carpet Adhesive claims refer to our website.

Contact details

Manufacture location Overseas

Legal and trading name of manufacturer Nexus Adhesives Pty Ltd **Legal and trading name of importer** importer Gilt Edge Industries

Importer address for service 110 Antigua Street

Addington, Christchurch 8240

Importer websitegiltedge.co.nz/Importer NZBN9429031908689Importer emailhelp@giltedge.co.nz

Importer phone number 0800445833

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Giltgrip 22 Carpet Adhesive is not subject to a warning on ban under <u>s26 of the Building Act</u>.

Signed for and on behalf of importer Gilt Edge Industries:

David Yang

David Yang
Chemist
Nov, 2023
Nexus Adhesives Pty Ltd
42 Healey Road, Dandenong South 3175, Victoria, Australia
Tel +61 3 9706 4022
www.nexusadhesives.com.au