GiltGrip 66 Pressure Sensitive Adhesive

BPIR Declaration

Version: 3

Designated building product: Class 1

Declaration

Gilt Edge Industries has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	GiltGrip 66 Pressure Sensitive Adhesive
Line	Acrylic emulsion
Identifier	GG66

Description

Giltgrip 66 Pressure Sensitive adhesive is Low in VOC and has been developed for the installation of vinyl composition tiles. It is also suitable for the installation of Carpet Tiles and slab underlays used in the double bond carpet installation. It has good plasticizer resistance.

Scope of use

Carpet Tile floor coverings. carpet underlay in double bond carpet installations.

Conditions of use

To be in accordance with The Australian/NZ Standard 1884 "Floor Coverings – Resilient Sheet and Tiles – Laying and Maintenance Practices" & Australian/NZ 2455:1:2007 Textile Floor Coverings. All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive applications 10 degrees C. Highly absorbent wooden or concrete subfloor surfaces are to be primed with a suitable Acrylic Primer prior to the application of adhesive. All concrete substrate floors should be tested for moisture content, according to the above Australian/NZ Standard prior to undertaking surface priming or installation of floorcoverings. For the installation of composition tiles & textured backed double bond underlays, apply adhesive using a 1.6mm x 1.6mm x 1.6mm "V" notched spreader with approx coverage of 5m² per litre. When installing Carpet Tiles and smooth backed Double Bond underlay, use a long nap roller with approx coverage of 7m² per litre. Store in dry, cool conditions away from direct sunlight.

Relevant building code clauses

Contributions to compliance

Building Regulations 1992 - Clause 2B-Durability GiltGrip 66, with only normal maintenance, will continue to satisfy the performance requirements of Building Regulations for 15 years.

Supporting documentation

The following additional documentation supports the above statements:

GiltGrip 661-https://giltedge.co.nz/download/tds-giltgrip-Technical Data202366?wpdmdl=9684&refresh=64f553411fe681693799233SheetI-https://giltedge.co.nz/download/mds-giltgrip-GiltGrip 66 Safety1-https://giltedge.co.nz/download/mds-giltgrip-Data Sheet202366?wpdmdl=9685&refresh=64f55341351d81693799233GiltGrip 66 VOC1-https://giltedge.co.nz/download/voc-giltgrip-report (Certification,202366?wpdmdl=9686&refresh=64f5534149a161693799233Test results)Test results

For further information supporting GiltGrip 66 Pressure Sensitive Adhesive claims refer to our website.

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Nexus Adhesives Pty Ltd
Legal and trading name of importer	Gilt Edge Industries
Importer address for service	110 Antigua Street
	Addington, Christchurch 8240
Importer website	giltedge.co.nz/
Importer NZBN	9429031908689
Importer email	help@giltedge.co.nz
Importer phone number	0800445833

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that GiltGrip 66 Pressure Sensitive Adhesive is not subject to a warning on ban under <u>s26 of the Building Act</u>.

Signed for and on behalf of Gilt Edge Industries:

David Yang

David Yang Chemist Nov, 2023 Nexus Adhesives Pty Ltd 42 Healey Road, Dandenong South 3175, Victoria, Australia Tel +61 3 9706 4022 www.nexusadhesives.com.au