## Giltgrip 88 PVC Tile & Vinyl Adhesive

### **BPIR Declaration**

Version: 1

**Designated building product:** Class 1

#### Declaration

Gilt Edge Industries has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

#### **Product/system**

Name Giltgrip 88 PVC Tile & Vinyl Adhesive

Line Acrylic emulsion based adhesive

**Identifier** GG88

#### Description

Giltgrip 88 PVC Tile & Vinyl Adhesive is a high performance, low VOC, acrylic based adhesive specifically designed for the installation of PVC planks and tiles. It is also ideal for the installation of commercial and domestic sheet vinyl.

#### Scope of use

Adhesive for vinyl flooring installations

#### Conditions of use

To be in accordance with the current Australian/NZ Standard 1884 -2013 "Floor Coverings – Resilient Sheet and Tiles – Laying and Maintenance Practices". All surfaces to be bonded shall be dry, smooth, sound and clean.

Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive applications should be greater than 10 degrees C. Highly absorbent wooden or concrete subfloor surfaces are to be primed with suitable Acrylic Primer prior to the application of adhesive. All concrete substrate floors should be tested for moisture content, according to the above Australian/NZ Standard prior to undertaking surface

priming or installation of floorcoverings.

Spread adhesive with a 1.6mm x 1.6mm x 1.6mm 'V' Notched trowel. Some domestic sheet vinyl may require a fine 1.6mm x 0.8 x .08 trowel to prevent adhesive 'show through'. Adhesive must be allowed to tack-up before floorcoverings is lowered. Tack-up time will depend upon atmospheric conditions and can be anywhere between 10-20 minutes. It is good practice to place a small piece of floorcoverings into the adhesive. When the floorcovering is pulled away, strings of adhesive should be apparent.

If no tack or holding power has developed, wait five minutes before rechecking every few minutes thereafter.

Complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roll weight, prior to the adhesive setting. Do not allow heavy traffic for 24 hours.

All seams for domestic vinyl should be seamsealed using suitable vinyl seam sealer.

#### Relevant building code clauses

#### **Contributions to compliance**

Building Regulations 1992 - Clause 2B-Durability GiltGrip 88, with only normal maintenance, will continue to satisfy the performance requirements of Building Regulations for 15 years.

#### **Supporting documentation**

The following additional documentation supports the above statements:

 GiltGrip 88
 1 https://giltedge.co.nz/download/tds-gg88-giltgrip 

 Technical Data
 2023
 88?wpdmdl=8597&refresh=6525d9e11b2f81696979425

 Sheet

 GiltGrip 88
 1 https://giltedge.co.nz/download/msds-gg88-giltgrip 

 Safety Data
 2023 88?wpdmdl=8598&refresh=6525d9e1336c01696979425

 Sheet

 GiltGrip 88 VOC
 1 https://giltedge.co.nz/download/voc-gg88-giltgrip 

 report (Test
 2023 88?wpdmdl=8599&refresh=6525d9e14b06a1696979425

results)

For further information supporting Giltgrip 88 PVC Tile & Vinyl Adhesive claims refer to our website.

#### **Contact details**

Manufacture location Overseas

Legal and trading name of manufacturer Nexus Adhesives Pty Ltd

**Legal and trading name of importer**Gilt Edge Industries

Importer address for service 110 Antigua Street

Addington, Christchurch 8240

Importer website <u>giltedge.co.nz/</u>

Importer NZBN 9429031908689

Importer email help@giltedge.co.nz

**Importer phone number** 0800445833

#### Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Giltgrip 88 PVC Tile & Vinyl Adhesive is not subject to a warning on ban under <u>s26 of the Building Act</u>.

Signed for and on behalf of **Gilt Edge Industries**:

# David Yang

David Yang
Chemist
Nov, 2023
Nexus Adhesives Pty Ltd
42 Healey Road, Dandenong South 3175, Victoria, Australia
Tel +61 3 9706 4022
www.nexusadhesives.com.au