

Giltgrip Double Bond 5.5mm (20m²)

BPIR Declaration

Version: V1.190826

Designated building product: Class 1

Declaration

Gilt Edge Industries Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Giltgrip Double Bond 5.5mm (20m ²)
Identifier	GGDB5.5

Description

Giltgrip Double Bond 5.5mm is a PU Foam underlay designed for Double Bond installation. It is produced in a continuous sheet with square trimmed edges. Double-stick system means rapid installation with no rucking or stretching of carpet.

Made from materials:

- Backing Material: Topside - Textron re-enforced paper.
- Downside - Non-woven Fabric.
- Composition - PU Foam

Dimension:

- Roll Width: 1370mm
- Roll Length: 14.6mtr.
- Roll Weight: 16.5kg
- Thickness: 5.5mm

Scope of use

Giltgrip Double Bond is a premium grade PU Foam double bond underlay for use in heavy contract commercial environments and high traffic areas including healthcare, aged care, hospitality, offices, and apartments. Increases thermal insulation for reduced energy consumption and warmer rooms. Improves Impact Insulation Class Ratings essential in reducing transference of noise. Suitable for all floor types, including heated slabs. Recyclable. Meets Australian Standard AS 4288-2003 for underlay durability. Pressure sensitive adhesive (underlay to subfloor adhesion option) for ease release up uplift in the future. All system adhesives and primers are manufactured in Australasia from solvent free, water-based formulations and are certified Low VOC and comply with NZ Green Star Adhesives /Sealants VOC limits.

Conditions of use

1. CONCRETE TREATMENT: Concrete Slab Treated with Protect Crete X200 Densi-Proof (at time of pour) to cure, densify, protect and moisture control.
2. Giltgrip Double Bond 5.5m GLUED TO SUBFLOOR: Carpet Adhesive: Giltgrip 22 or Roberts 80or Pressure Sensitive Adhesive: Giltgrip 66 or Polymer 999.
3. CARPET TILES GLUED TO Giltgrip Double Bond 5.5m Pressure Sensitive Adhesive: Giltgrip 66 or Polymer 999 Or Carpet Adhesive (If required): Giltgrip 22 or Roberts 80

Contributions to compliance

Building Regulations 1992 - Clause 2B-Durability Giltgrip Double Bond Underlay, with only normal maintenance, will continue to satisfy the performance requirements of Building Regulations for 10 years or for the life of the installed carpet.

Supporting documentation

The following additional documentation supports the above statements:

Giltgrip Double Bond 5.5 - Technical Data Sheet	February 2026	https://giltedge.co.nz/download/giltgrip-double-bond-5-5-tds
Giltgrip Double Bond 5.5 - Acoustic Test Result	February 2026	https://giltedge.co.nz/download/giltgrip-double-bond-5-5-acoustic-tests?wpdmdl=12554&ind=1787014095701&refresh=6a4204fd&filename=GG-DB-5.5-T2601-1-ATS.pdf
Giltgrip Double Bond 5.5 - NZWTA Test Result	August 2024	https://giltedge.co.nz/download/giltgrip-double-bond-5-5-performance-test

For further information supporting Giltgrip Double Bond 5.5mm (20m²) claims refer to our website.

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	HANGZHOU JIANGDONG CARPET UNDERLAY CO.,LTD.
Legal and trading name of importer	Gilt Edge Industries Limited
Importer address for service	110 Antigua Street Addington
Importer website	www.giltedge.co.nz
Importer NZBN	9429031908689
Importer email	help@giltedge.co.nz

Importer phone number

0800445833

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Giltgrip Double Bond 5.5mm (20m²) is not subject to a warning on ban under [s26 of the Building Act](#).

GILT EDGE INDUSTRIES LIMITED

110 Antigua Street Addington New Zealand

0800445833 | www.giltedge.co.nz

BPIR Ready selections

Category: Other (custom)
