



**GILT EDGE
INDUSTRIES LIMITED**

FLOORING PREPARATION AND INSTALLATION SPECIALISTS

**FLOOR
PREPARATION
PRODUCT
CATALOGUE**

**EVERY FLOORING INSTALLATION
DESERVES THE "GILT EDGE" FINISH**

August 2025

PRIMERS



Uzin PE 260 Primer (UZPE2605) - Multi-use, highly concentrated dispersion primer with excellent adhesion on dense and absorbent substrates. Can be used diluted or undiluted depending on the substrate.

- * Can be used on almost all substrates
- * Very good adhesion
- * Can also be diluted with water depending on the substrate

Coverage
Wet Primer per 10kg
 30gms/m² when diluted 4:1
Dry Primer per 10kg
 40gms/m² when diluted 3:1



Uzin PE 280 Primer (UZPE280) Film smoothing primer for smooth non porous surfaces. Rapid cure. For applications over sound and well bonded existing adhesive residues and screeds. For priming substrates treated with Uzin epoxy based moisture barriers and primers. Primer for timber prepared timber substrates plus T&G. 45 minute cure time.

Coverage
 40-150gms/m²



Uzin PE 460 Primer (UZPE460) - 2 part epoxy primer for damp or weak substrates. Heavy duty primer for domestic, commercial and industrial use. Maybe blended with aggregates to produce a durable mortar system. Primer for substrates with below 90% moisture content and reducing. Primer for KR430 and KR421 in exterior situations.

Coverage
 30 m² per 10kg Kit
 (as a primer)



Roberts Universal Primer 5L (RFPUP5) - This universal primer is a rapid drying solvent free low VOC water based acrylic primer. For use over porous and non porous substrates such as existing tiles, old paint (with the exception of oil based paints) vinyl adhesive, vinyl tiles, carpet adhesive residue, metal surfaces, sealed or burnished concrete floors. Is compatible with cement based ceramic tile adhesive. Can be applied internally or externally over clean dry surfaces.

Coverage
 Approx 5 m² to 10m² per Litre



Uzin PE414 Biturbo (UZPE414)
 1-Component PUR Rapid Primer
 Fast and reliable priming
 One-component reactive resin primer for wood flooring and floor covering work
 No mixing, fast, high coverage, reliable.

Coverage
 80 - 150 g/m² per coat

PRIMERS CONTINUED



UzinPE650 (UZPE650) Cementitious, extremely fast drying 1-component Flex-Filler-Primer with hard elastic properties for substrates in need of renovation or on wooden floorboards. Extremely fast drying, high formability due to “hard-elastic” properties and excellent adhesion to the substrate

Coverage

80-240m² per 16kg bag

SELF LEVELLING COMPOUNDS



Uzin NC 160 (UZNC16020) - Self Levelling water mixed compound. 1.5mm-20mm thickness (5L water). Interior use only. For preparation prior to installation of all floor coverings. **Not for under solid timbers.** 30MPA


Coverage

4.75 m² per 20kg bag @ 3.00mm thick

1.40 m² per 20kg bag @ 10.00mm thick

(Product can be extended with Uzin sand 2:1)

INDENT ONLY



Uzin NC 170 Level Star (UZNC17020) - Self Levelling water mixed compound. High strength. High performance and high flow characteristics. Thickness unlimited (5.25L water). Interior use only. **For preparation prior to installation of all floor coverings including solid timber flooring.** 35-40 MPA

Coverage

4.75m² per 20kg bag @ 3.00mm thick

1.40m² per 20kg bag @ 10.00mm thick

(Product can be extended with Uzin sand 2:1)

INDENT ONLY



Uzin NC 168SP High quality smoothing and levelling of substrates for the subsequent installation of all types of floor coverings including solid and engineered wood flooring systems. Green-Star Certified with a low VOC Content

Coverage

1 mm thick -1.5 kg/m²

3 mm thick -4.5 kg/m²

10 mm thick -15.0 kg/m²



Uzin NC 164SP Smoothing and levelling of substrates for the subsequent installation of textile and resilient floor coverings as well as engineered timber floors. For thicknesses from 1 to 10 mm (with aggregates up to 25 mm) Green-Star Certified with a low VOC content

1 mm thick -1.5 kg/m²

3 mm thick -4.5 kg/m²

10 mm thick -15.0 kg/m²



Uzin NC157SP Self-smoothing bulk filling levelling compound for the subsequent installation of most floor coverings including some wood flooring systems. For thicknesses from 3 to 50 mm (with aggregates up to 70 mm) Green-Star Certified with a low VOC content.

Coverage

3 mm thick 5.1 kg/m²

10 mm thick -17.0 kg/m²

SKIM COAT / PATCH REPAIR



Uzin NC 888 (UZNC888) - Very fine and rapid setting flushing compound that finishes to a fine finish edge. Excellent bonding properties to a very wide range of substrates with or without primer. Ideal for repair of small substrate imperfections. For thickness up to 4.0mm. Most installations can be laid on after 30 minutes. Interior use only. Large water ratio. Use Progress sand as soon as dry.

Coverage

4.1 m² per 4.5kg bag @ 1.00mm thick
1.0 m² per 4.5kg bag @ 4.00mm thick



Roberts 35 Fine Patch (RFPFP35) - Roberts Fine Patch 35 is a fast drying cementitious underlayment designed for smoothing ridges, patching cracks or holes and feather-edge transitions. Applied as a feather edge, expect to gain anything up to 30sqm, depending on texture of substrate.

Coverage

8 m² per 10kg pail @ 1.00mm thick



Uzin NC181 Low-slump and rapid repair mortar for any range of thickness. Ready to accept floor coverings after 60 minutes*, hydraulic setting, fine grain and no visible patching marks

Coverage

1 mm thick - 1.5 kg/m²
3 mm thick - 4.5 kg/m²
10 mm thick - 15.0 kg/m²

SPECIAL SCREED



Uzin NC196 (UZNC19620 - Very low emission, rapid setting, cementitious and fibre reinforced smoothing compound for the thickness range from 3 – 40 mm in interior locations. Suitable for surface smoothing and levelling work. For producing smooth surfaces with good absorbency for floor covering work as well as for the installation of tiling and natural stone. Suitable for plywood and most types of construction board flooring.

Coverage

Approx 4m² at 3mm per bag

SUBSTRATE REPAIR



Uzin KR 516 (UZKR516) - Low odour casting and bonding resin for the quick restoration of cracks as well as bonding, fillings and repairs. Can be used in sensitive areas, no processing odour. No stirring tools required. Can be quickly worked on, short waiting time.

Coverage

Approx. 100ml/running metre joint at 4 x 25mm
2 x 300ml plastic bottles per unit



Gilt Grip Repair Epoxy Kit 13kg (GGEPOXY13) - is an epoxy system formulated to provide damage repair to concrete, wood and other common building materials. Structural adhesive—repair and refill of cracks in concrete and common building products. High impact strength areas—ramps, joint nosing's. Fills voids in damaged or spalled concrete. Grouting starter bars, load bearing bolts and base plates.

Refer to Gilt Edge Industries Ltd Technical Data Sheet within kit.

Kit includes: Resin, Hardener, Sand, Gloves & spread rate chart.

MOISTURE CONTROL



Protect Crete Moisture Fix 15L (PCMFIX)

Moisture Fix is a single pack one application, pour and spread, or low pressure spray system that deeply penetrates new or existing concrete, providing permanent water proofing, curing and protection.

Coverage

Freshly Placed Concrete: By Spray
Minimum 5m² per litre.
Existing Concrete: By Spray
Minimum 5m² per litre.
By Pour Minimum 4m² per litre.



Protect Crete Densi Proof 20L (PCX200)

Densi proof is a single pack one application spray on system that deeply penetrates new or existing concrete, provides permanent waterproofing curing and protection.

Coverage

Freshly Placed Concrete:
Minimum 5m² per litre.
Existing Concrete: Minimum
5m² per litre.

MOISTURE CONTROL



Bostik Moisture Seal (BOSMS) - is a 2 part water based epoxy coating designed as a moisture and vapour barrier membrane to prevent water seepage and permeation through concrete floors. The product shows excellent adhesion and acts as a surface preparation for subsequent adhesives when laying floor coverings of all kinds.

Coverage

5 m² per Litre (Single Coat)

20 m² per 8 Litre Kit (Two Coats)

50 m² per 20 Litre Kit (Two Coats)

Note: Finished system to be applied in two coats.



Selleys Liquid Nails VBS (SLNVBS3.6) - A highly cross linked, pigmented, two pack epoxy vapour barrier system. For sealing concrete floor slabs to reduce the amount of water vapour emanating from the concrete. Suitable for use on concrete slabs prior to using Selleys Liquid Nails Direct Stick polyurethane timber flooring adhesive to lay timber flooring.

Coverage

One full pack (3.6 Litre) is sufficient for 20m². (6 m² per Litre)

Note: Two coats maybe required in the case of very porous concrete.



Uzin PE414 Biturbo (UZPE414)

1-Component PUR Rapid Primer

Fast and reliable priming

One-component reactive resin primer for wood flooring and floor covering work

No mixing, fast, high coverage, reliable.

APPLICATIONS:

Prior to installation of wood flooring with UZIN reactive resin adhesives (pay attention to drying times)

On dense or absorbent substrates

On moisture-sensitive substrates

Primed with UZIN PE 280 prior to levelling work

Coverage

80 - 150 g/m² per coat

WATERPROOFING



Flexi Seal PUD Waterproof Membrane 15L (RFPWFLEX15)

Flexi Seal PUD is a blue, water based polyurethane modified , flexible water proofing membrane. Can be used over concrete, render, rendered brickwork, block work, fibre cement, plywood and particle board surfaces. Can be used for internal or external waterproofing applications.

Coverage
1 m2 per 1.5L per two coats

ACCESSORIES



Silicate Sand 3-8mm 25kg (UZ10606) - Fire dried quartz with gram size 0.3—0.8mm as a filler and four surface gritting. For filling and thickening pouring and bonding resins to give a homeogenous mortar. Produces a gritted surface. Fills and adjusts consistency. For interior and exterior use.



Uzin Levelling Pins (UZ61834) - Plastic self adhesive height measurement pins for use when pouring levelling compounds.



Uzin Reinforcement Fibre 250gm
(UZ11725) - Alkaline resistant glass fibre for increasing the structural strength of self levelling smoothing compounds.

ACCESSORIES



5L Measuring Jug (RFPMJ) - Easy measurement of water quantity for powder products.



Uzin Water Measuring Bucket (UZ87607)

Plastic bucket with printed litre scale. Ideal for measuring the correct water quantity for powder products.



Uzin Blue Mixing Bucket 30L (UZ9191)—Great size and strength. Easy handling for mixing of levelling compounds.

ACCESSORIES



Wolff Professional Levelling Compound Rake (W52298) - For applying self levelling compounds.

R2 Blade (W13396) - 2.0mm Approx spread rate.

R3 Blade (W51546) - 3.0mm Approx spread rate.



Wolff Professional Spike Roller - For venting compounds and coatings. Splash guard included. Telescopic handle connector.

25cm (W14272) with 21mm pin length

50cm (W13636) with 31mm pin length



Wolff Professional Spike Shoes (W51549). For walking on coated or filled substrates and surfaces. Included is 1 x spare set of nails and 2 x spare straps. Once size fits all.



Wolff Specialised Stirrer KR Type (W13606) - Very high shear forces, easy to clean, suitable for viscous adhesive or seals and gypsiferous or bituminous materials. Ideal for mixing levelling compounds. Prevents clotting.



Wolff Professional Smoothing Trowel (W56203)

280mm x 135mm Blade.

Solid Construction and ergonomic control handle.



Wolff Professional Levelling Compound Trowel (W56204)

500mm x 135mm Blade.

Solid construction with ergonomic control handle.

ACCESSORIES



1600W Electric Hand Mixer (TM678281) - This mixer is a heavy duty floor preparation mixer. It is used for mixing flooring compounds quickly and thoroughly.

Double Handle

140mm Paddle

40-90L Volume Capacity



Porta Mix (Hippo) & Mix Paddle (PPPM) - Mixes, delivers and spreads material quickly with excellent control. Handles wide range of construction compounds. Easy operation by one person. Reduces time, effort and labour costs. Thorough mixing, blending and replacement without mess. Dust extraction port for dust control. Easy to clean out. Bowl capacity 6 x 20kg mix plus water (85L/160kg)



www.giltedge.co.nz

EMAIL: help@giltedge.co.nz

FREE PHONE: 0800 445 833