

# GILTGRIP 777 FAST BOND NEEDLE PUNCH

## BPIR Declaration

Version: V2.01102024

---

### Designated building product: Class 1

---

### Declaration

Bostik New Zealand Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

---

### Product/system

|            |                                     |
|------------|-------------------------------------|
| Name       | GILTGRIP 777 FAST BOND NEEDLE PUNCH |
| Identifier | GG777                               |

---

### Description

Giltgrip 777 is a solvent based trowel applied adhesive for bonding synthetic backed carpet on to concrete or timber. Giltgrip 777 has an exceptionally strong initial grab and gap filling to ensure the best possible bond to most interior surfaces. It exhibits good water-resistant bonds and water damage even after 5 hours will not affect the bond even if the adhesive becomes flooded.

SIZE:4L and 20L.

Coverage = 2 m<sup>2</sup>/L

---

### Scope of use

Giltgrip 777 is manufactured for use on :

- Synthetic backed carpet onto concrete
- Synthetic backed carpet onto timber

Giltgrip 777 smart advantages:

- High initial grab

- Good water resistance
  - Gap filling
- 

## Conditions of use

Store in a cool dry place below 25°C and out of direct sunlight. Store away from naked flame or sources of heat. Shelf life is 12 months from the date of manufacture when stored as directed.

### **SURFACE PREPARATION:**

Ensure all surfaces are clean and dry. Free from all loose paint, dust, grease and release agents.

### **APPLICATION :**

Remove all sources of ignition. Stir well before use. Apply adhesive over the floor surfaces using a 2 or 3mm notched trowel. Rough, uneven surfaces will require more adhesive - select a notched trowel to give sufficient coverage. Place the carpet onto the wet adhesive. This must be carried out within 5 to 10 minutes of applying (see LIMITATIONS). Apply even pressure over the carpet with a heavy roller to facilitate adhesive transfer and bonding. Do not roll excessively as this can force the wet adhesive into the weave of the carpet and poor adhesion may result due to insufficient adhesive thickness. After 30 minutes, pass the roller over the carpet again, especially around the joints and edges to ensure a good bond. This is important to ensure that the bond is properly formed.

### **LIMITATIONS:**

- Not suitable on CCA treated timber.
- Do not use in fully exposed exterior situations.
- Do not exceed the open time of 5 to 10 minutes depending on atmospheric conditions. Exceeding the open time will result in lower adhesion due to poor adhesive transfer and wetting on the carpet backing.
- Do not roll excessively as this can force the wet adhesive into the weave of the carpet and poor adhesion may result due to insufficient adhesive thickness.

### **CLEANING:**

Bostik No. 2 or 3 Solvent for cleaning. For thinning use Bostik No.3 Solvent ONLY. Use Bostik Handy Wipe towels to remove adhesive from skin.

### **DISPOSAL:**

Dried, empty containers may be disposed via local landfill. If spilt, absorb with clay, sand or earth. Collect and seal in properly labeled metal container. Dispose of according to local authority regulations. Do not dispose of down drains or into local waterways.

## PRECAUTIONS IN USE:

Complete details on each of the products mentioned are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that all concerned read the appropriate Safety Data Sheets.

**HIGHLY FLAMMABLE - KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME  
KEEP OUT OF REACH OF CHILDREN KEEP CLOSED WHEN NOT IN USE**

## FIRST AID:

Swallowed: Do not induce vomiting, give a glass of water and contact a doctor immediately. Skin: Remove contaminated clothing, wash with warm soapy water. Do not scrub. Inhaled: Remove person to fresh air. Get medical advice if breathing becomes difficult. If inhaled to excess, remove from contaminated area - apply artificial respiration if not breathing. Eyes: Hold open and flood with water for at least 15 minutes. Get medical advice. For emergency information contact the National Poisons Information Centre, phone 0800 764 766 (0800 POISON) or CHEMICALL, phone 0800 243 622. Smart help

---

## Contributions to compliance

Building Regulations 1992 - Clause 2B-Durability GiltGrip 777, with only normal maintenance, will continue to satisfy the performance requirements of Building Regulations for 15 years.

---

## Supporting documentation

The following additional documentation supports the above statements:

|                                         |                                     |                                                                                                                                                                                                                             |
|-----------------------------------------|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GG777 Technical Data Sheet</b>       | Version 27<br>February 2019         | <a href="https://giltedge.co.nz/download/tds-gg777-giltgrip-777?wpdmdl=8588&amp;refresh=65688365114e21701348197">https://giltedge.co.nz/download/tds-gg777-giltgrip-777?wpdmdl=8588&amp;refresh=65688365114e21701348197</a> |
| <b>GG777 Material Safety Data Sheet</b> | Version 29 -<br>September -<br>2024 | <a href="https://giltedge.co.nz/download/msds-g777-giltgrip-777?wpdmdl=8589&amp;refresh=66faec74e13981727720564">https://giltedge.co.nz/download/msds-g777-giltgrip-777?wpdmdl=8589&amp;refresh=66faec74e13981727720564</a> |

For further information supporting GILTGRIP 777 FAST BOND NEEDLE PUNCH claims refer to our website.

---

### Contact details

|                                        |                                 |
|----------------------------------------|---------------------------------|
| Manufacture location                   | New Zealand                     |
| Legal and trading name of manufacturer | Bostik New Zealand Limited      |
| Manufacturer address for service       | 19 Eastern Hutt Road<br>Wingate |
| Manufacturer email                     | nzsales@bostik.com              |
| Manufacturer phone number              | 04-567 5119                     |
| Manufacturer NZBN                      | 9429039292674                   |

---

### BPiR Ready selections

Category: Other (custom)