Product Introduction to NZ.

Product Code: 12249

Uzin KE68T Single component Hybrid adhesive.

Uzin KE68T adhesive is a single component high performance 'urethane type' adhesive that is suited to a large range of installations requiring high dimensional stability in extreme conditions such as sun-drenched areas, high point loading and areas requiring water-resistance from the top of the floorcoverings (wet areas).

Uzin KE68T adhesive is suited to installations on floors and walls.

Applications:

- Rubber tiles up to 4.0mm (e.g Norament)
- Luxury Vinyl Tiles in all areas including areas subjected to direct sunlight with constant stability available at temperatures NOT exceeding 50deg C.
- For PVC and CV tiles- on floors and walls.
- For granulate recycled rubber flooring systems (Regupol etc)
- Linoleum tiles up to 4.0mm thick.
- Indoor entrance mats subjected high traffic and exposure to water.
- Artificial grass installations and sports flooring.
- For heavy wear commercial and industrial applications.

Key features:

- Single component Ready to use with no mixing required.
- Solvent free.
- Compliments the range: KE66 and KR430
- Opague/White coloured adhesive.
- Easy to trowel.
- Excellent high temperature stability.
- Very high cured bond strength.

Note:

- Surface water must be removed within 24 hours.
- For longer term/sustained exposure to surface water refer to Uzin KR430 2-part adhesive.



Oct 2021

EMAIL: help@giltedge.co.nz | FREE PHONE: 0800 445 833 | www.giltedge.co.nz

