



SEAMLESS FLOORING SYSTEMS

LAMINATE & HYBRID (LOOSE LAID) FLOORING OVERLAY ON TIMBER SUBFLOORS WET ROOMS WATERSPLASH INSTALLATION SYSTEM ALTERNATIVE SOLUTION - E3/AS1 BUILDING CODE- INTERNAL MOISTURE FOR FINISHES TO FLOORS: KITCHENS, TOILETS AND LAUNDRIES

Must be read in conjunction with E3/AS1 November 4th 2021 Building Code. The following information is only to assist in the Alternative Solutions options for the installer. It is essential the Laminate supplier provides their own documentation as to the floorcoverings suitability as required by E3/AS1.

- 1 Composite Timber Subfloor Sheet Type: Particle Board/Plywood/Strand board.
NB: For Cross Laminated Timber (CLT)/Parallel Laminated Timber (PLT) Type Construction Panel Subfloors: Contact Gilt Edge Technical for project specific system advice and selections.
- 2 **OPTION A.)** Sheet Overlay: Trimtec Hardboard 5.5mm thickness
OPTION B.) Levelling System: UZIN PE280 / UZIN NC157 SP minimum 3mm thickness
- 3 Proprietary Moisture Resistant Underlayment (as per systems recommended by the Laminate or Hybrid Flooring Supplier.)
- 4 Interlocking Laminate or Hybrid Flooring System.

