



LUXURY VINYL TILE (LVT) WET ROOMS WATERSPLASH INSTALLATION SYSTEM ALTERNATIVE SOLUTION - E3/AS1 BUILDING CODE- INTERNAL MOISTURE FOR FINISHES TO FLOORS: BATHROOMS

Must be read in conjunction with E3/AS1 (2nd edition, Amendment 7) Building Code. The following information is based on adhesive performance only to assist in the Alternative Solutions options for the installer. It is essential the LVT supplier provides their own documentation as to the floor coverings suitability as required by E3/AS1.

- 1 Concrete substrate treated with Protect Crete Densi-Proof (Optional site specific as required.)
- 2 Subfloor Preparation Systems
Subfloor primed with Uzin PE280 (Non-porous) or Uzin PE260 (Porous)
OPTION 1.) Uzin NC164 SP or NC168 SP Levelling Compound
OPTION 2.) Uzin NC888S/NC888F Skim Coat
- 3 **ADHESIVE OPTION 1:** Uzin KE68T 1-Component STP Adhesive
ADHESIVE OPTION 2: Uzin KR430 2-Component PUR Adhesive
- 4 Luxury Vinyl Tile (LVT) as Specified Refer to supplier/manufacturer regarding E3/AS1 code compliance.

