



SEAMLESS FLOORING SYSTEMS

LUXURY VINYL TILE (LVT) WET ROOMS CONTAINMENT INSTALLATION SYSTEM ALTERNATIVE SOLUTION- E3/AS1 BUILDING CODE - INTERNAL MOISTURE FOR FINISHES TO FLOORS:

Containment - water from accidental overflow from a sanitary fixture that "could damage an adjoining household unit or other property". The affected areas are defined as having a sanitary fixture (e.g. toilet, sink, shower or bath) or sanitary appliance (e.g. washing machine or dishwasher.)

Must be read in conjunction with E3/AS1 (2nd edition, Amendment 7) building Code. The following information is based on adhesive performance only to assist in the Alternative Solutions options for the installer. It is essential the LVT supplier provides their own documentation as to the floor coverings suitability as required by E3/AS1

- 1 Concrete Subfloor treated with Protect Crete Densi-Proof or Moisture-Fix at time of pour
- 2 **(OPTIONAL)** RLA Flexi-Seal P.U.D. Waterproof Membrane pre-primed with Roberts Universal Acrylic
- 3 Prime membrane surface using Uzin PE280 Primer
- 4 Subfloor Preparation Systems Options (Site specific as required.)
OPTION A: Uzin NC 164 SP Levelling Compound
OPTION B: Uzin NC181SP
OPTION C: Uzin NC888S/NC888F Skim Coat
- 5 **ADHESIVE OPTION 2:** Uzin KE68T 1-Component Hybrid Adhesive
ADHESIVE OPTION 3: Uzin KR430 2-Part Adhesive
- 6 Luxury Vinyl Tile (LVT) as Specified: Refer to supplier/
manufacturer regarding E3/AS1 code compliance.

