



# SEAMLESS FLOORING SYSTEMS

## LUXURY VINYL TILE (LVT) ON TIMBER SUBFLOORS WET ROOMS WATERSPLASH INSTALLATION SYSTEM ALTERNATIVE SOLUTION - E3/AS1 BUILDING CODE- INTERNAL MOISTURE FOR FINISHES TO FLOORS: BATHROOMS

Must be read in conjunction with E3/AS1 (2nd edition, Amendment 7) Building Code. The following information is based on adhesive performance only to assist in the Alternative Solutions options for the installer. It is essential the LVT supplier provides their own documentation as to the floorcoverings suitability as required by E3/AS1.

- 1 Code Compliant Composite Timber Sheet Type  
**NB: For Cross Laminate Timber (CLT)/Parallel Laminated Timber (PLT) Type Construction Panel, Strandfloor Subfloors: Contact Gilt Edge Technical for project specific system advice and selections.**
  - 2 **OPTION A.)** Sheet Overlay: Trimtec Hardboard 5.5mm thickness  
**OPTION B.)** Levelling System: UZIN PE280 primer with 3mm minimum thickness UZIN NC157 SP / NC168 SP Levelling Compound
  - 3 **ADHESIVE OPTION 1:** Uzin KE68T 1-Component STP Adhesive
  - 4 **ADHESIVE OPTION 2:** Uzin KR430 2-Component PUR Adhesive
- Luxury Vinyl Tile (LVT) as Specified: Refer to supplier/manufacturer regarding E3/AS1 code compliance.

