

Revision date 29-Sep-2024

This safety data sheet was created pursuant to the requirements of: GHS: The Globally Harmonized System of Classification and Labeling of Chemicals

GILTGRIP 777

Revision Number 1.01 Supersedes date 10-May-2021

Section 1: Identification

Product identifier

Product Name GILTGRIP 777

Other means of identification

Recommended use of the chemical and restrictions on use

Recommended use Adhesives

Uses advised against No information available

Details of the supplier of the safety data sheet

 Supplier
 Manufacturer

 Bostik New Zealand Limited
 Bostik New Zealand Limited

Bostik New Zealand Limited 19 Eastern Hutt Road Wingate, Lower Hutt, New Zealand

 Lower Hutt, New Zealand
 Lower Hutt, New Zealand

 Tel: 04-567 5119
 Tel: 04-567 5119

 Fax: 04-567 5412
 Fax: 04-567 5412

E-mail address SDS.AP@Bostik.com

Emergency telephone number

Emergency Telephone 24 Hr: 0800 243 622

International +64 4 917 9888 Poison Centre: 0800 764 766

19 Eastern Hutt Road Wingate,

Section 2: Hazard identification

GHS Classification

Flammable liquids	Category 2
Aspiration hazard	Category 1
Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Acute aquatic toxicity	Category 1
Chronic aquatic toxicity	Category 1

Label elements



New Zealand Page 1 / 13

GILTGRIP 777 Revision date 29-Sep-2024
Revision Number 1.01 Supersedes date 10-May-2021

Signal word

Danger

Hazard statements

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/clothing and eye/face protection

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Avoid release to the environment

Ground and bond container and receiving equipment

Use non-sparking tools

Take action to prevent static discharges

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Keep cool

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Spill

Collect spillage

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

In use, may form flammable/explosive vapor-air mixture.

Section 3: Composition/information on ingredients

Chemical name	CAS No.	Weight-%
Heptane	142-82-5	20- <40
Kaolin	1332-58-7	10 - <20
Cyclohexane	110-82-7	10 - <20
Methylcyclopentane	96-37-7	1 - <5
Octane	111-65-9	1 - <3

New Zealand Page 2 / 13

GILTGRIP 777 Revision Number 1.01 Revision date 29-Sep-2024 Supersedes date 10-May-2021

Chemical name	CAS No.	Weight-%
Toluene	108-88-3	1 - <3
	T	

Non-hazardous ingredients	Proprietary	Balance
---------------------------	-------------	---------

Section 4: First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Inhalation Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing

has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Get medical attention if irritation develops and persists.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth

resuscitation. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapor

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Effects of Exposure May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility.

May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed

unless the risk is justified by the presence of additional toxic substances.

Section 5: Fire-fighting measures

Suitable Extinguishing Media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical

New Zealand Page 3 / 13

GILTGRIP 777 Revision date 29-Sep-2024 **Revision Number** 1.01 Supersedes date 10-May-2021

Specific hazards arising from the chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated

fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products

Carbon oxides. Hydrocarbons. Silicon dioxide.

Special protective actions for fire-fighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See **Personal precautions**

> section 8 for more information. Avoid contact with skin, eves or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or **Environmental precautions**

spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Stop leak if you can do it without risk. Do not touch or walk through spilled material. A **Methods for containment**

vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand

or other non-combustible material and transfer to containers for later disposal.

Take precautionary measures against static discharges. Dam up. Soak up with inert Methods for cleaning up

absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage

Precautions for safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from Advice on safe handling

> heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing

New Zealand Page 4 / 13

GILTGRIP 777 Revision Number 1.01 Revision date 29-Sep-2024 Supersedes date 10-May-2021

and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials. Protect from

moisture.

Recommended storage

temperature

Keep at temperatures between $\,$ 41 and 77 °F / 5 and 25 °C.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Section 8: Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	New Zealand	ACGIH TLV	United Kingdom	Australia
Heptane	TWA: 400 ppm	TWA: 400 ppm	TWA: 500 ppm	TWA: 400 ppm
142-82-5	TWA: 1640 mg/m ³	STEL: 500 ppm	TWA: 2085 mg/m ³	TWA: 1640 mg/m ³
	STEL: 500 ppm		STEL: 1500 ppm	STEL: 500 ppm
	STEL: 2050 mg/m ³		STEL: 6255 mg/m ³	STEL: 2050 mg/m ³
Kaolin	TWA: 10 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 10 mg/m ³
1332-58-7	TWA: 2 mg/m ³	particulate matter	STEL: 6 mg/m ³	
		containing no asbestos		
		and <1% crystalline		
		silica, respirable		
		particulate matter		
Cyclohexane	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
110-82-7	TWA: 350 mg/m ³	/A: 350 mg/m³		TWA: 350 mg/m ³
	STEL: 300 ppm		STEL: 300 ppm	STEL: 300 ppm
	STEL: 1050 mg/m ³		STEL: 1050 mg/m ³	STEL: 1050 mg/m ³
Octane	TWA: 300 ppm	TWA: 300 ppm	-	TWA: 300 ppm
111-65-9	I-65-9 TWA: 1400 mg/m ³			TWA: 1400 mg/m ³
	STEL: 375 ppm			STEL: 375 ppm
	STEL: 1750 mg/m ³			STEL: 1750 mg/m ³
Toluene	TWA: 20 ppm	TWA: 20 ppm TWA: 20 ppm		TWA: 50 ppm
108-88-3	8-88-3 TWA: 75 mg/m ³ Ototox		TWA: 191 mg/m ³	TWA: 191 mg/m ³
	STEL: 100 ppm cause hearing disor		STEL: 100 ppm	STEL: 150 ppm
	STEL: 377 mg/m ³		STEL: 384 mg/m ³	STEL: 574 mg/m ³
	Sk*		Sk*	

Biological occupational exposure limits

Chemical name	New Zealand	ACGIH
Cyclohexane	-	50 mg/g creatinine - urine (1,2-Cyclohexanediol) -

New Zealand Page 5 / 13

GILTGRIP 777 Revision date 29-Sep-2024 **Revision Number** 1.01 Supersedes date 10-May-2021

110-82-7		end of shift at end of workweek
Toluene	0.03 mg/L - urine (Toluene) - end of exposure or	0.02 mg/L - blood (Toluene) - prior to last shift of
108-88-3	end of shift	workweek
	0.3 mg/g creatinine - urine (O-Cresol) - end of	0.03 mg/L - urine (Toluene) - end of shift
	exposure or end of shift	0.3 mg/g creatinine - urine (o-Cresol with
	·	hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls Showers

> Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Tight sealing safety goggles. Eye/face protection

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

No protective equipment is needed under normal use conditions. If exposure limits are Respiratory protection

exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Liquid Physical state **Appearance** Paste Viscous Color Brown Odor Solvent

Odor threshold No information available

Property Values Remarks • Method

No data available Not applicable Insoluble in water

Melting point / freezing point No data available None known 50 °C

Initial boiling point and boiling

range

-15 °C

Evaporation rate No data available None known **Flammability** No data available Flammable liquid Flammability Limit in Air None known

Upper flammability or explosive 7.5

limits

Flash point

Lower flammability or explosive 1.1

limits

Vapor pressure <110 kPa None known Relative vapor density No data available None known Relative density No data available None known

Water solubility Insoluble in water

No data available None known Solubility(ies) **Partition coefficient** No data available None known **Autoignition temperature** No data available None known **Decomposition temperature** None known None known

No data available Kinematic viscosity **Dynamic viscosity** No data available

No information available. **Explosive properties**

New Zealand Page 6 / 13

GILTGRIP 777 Revision date 29-Sep-2024 **Revision Number** 1.01 Supersedes date 10-May-2021

No information available. **Oxidizing properties**

Other information

No information available Softening point Molecular weight No information available **VOC** content No information available

Liquid Density 1.15

No information available **Bulk density**

Particle characteristics

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stable under normal conditions. Stability

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Protect from moisture.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Incompatible materials

Hazardous decomposition products

Hazardous decomposition

products

Carbon oxides.

Section 11: TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can

> produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the

substance or mixture is not available. Causes skin irritation. (based on components).

Specific test data for the substance or mixture is not available. Potential for aspiration if Ingestion

New Zealand Page 7 / 13

Revision Number 1.01 Revision date 29-Sep-2024
Supersedes date 10-May-2021

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may

cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause

redness and tearing of the eyes. Inhalation of high vapor concentrations may cause

symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 >5000 mg/kg

 ATEmix (dermal)
 >5000 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-vapor)
 >20 mg/l

 ATEmix (inhalation-dust/mist)
 94.50 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Heptane	LD50 > 5000 mg/Kg (rattus)	= 3000 mg/kg (Oryctolagus	=103 g/m ³ (Rattus) 4 h
		cuniculus)	
Kaolin	LD50 (Rattus) > 2000 mg/kg	> 5000 mg/kg (Rattus)	1.5 mg/l 4hr
Cyclohexane =12705 mg/kg (Rattus)		> 2000 mg/kg (Oryctolagus	>9500 ppm (Rattus) 4 h
		cuniculus)	
Octane	>5000 mg/Kg (Rattus)	-	=118 g/m³ (Rattus) 4 h =
			25260 ppm (Rattus) 4 h >
			23.36 mg/L (Rattus) 4 h
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus	>20 mg/L (Rattus) 4 h
		cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Toluene (108-88-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No.	Rabbit	Dermal			Irritant
440/2008 Annex B 4					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Heptane (142-82-5)

Method	Species	Results
OECD Test No. 473: In vitro Mammalian	Rat, in vitro	Not mutagenic
Chromosome Aberration Test		
OECD Test No. 471: Bacterial Reverse		Not mutagenic in AMES Test
Mutation Test		

Toluene (108-88-3)

New Zealand Page 8 / 13

GILTGRIP 777 Revision Number 1.01 Revision date 29-Sep-2024 Supersedes date 10-May-2021

Method	Species	Results
Regulation (EC) No. 440/2008, Annex, B.13/14	Salmonella typhimurium	Not mutagenic
(Ames test)	·	
OECD Test No. 476: In Vitro Mammalian Cell	Mouse	Not mutagenic
Gene Mutation Tests using the Hprt and xprt		-
genes		

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

The table below indicates which each agoney has never any ingreation as a sarollogen.			
Chemical name	New Zealand	IARC	
Toluene - 108-88-3	-	Group 3	

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity Classification based on data available for ingredients. Suspected of damaging fertility or

the unborn child.

Toluene (108-88-3)

	Species	Results
OECD 407	in vivo	Reproductive toxicant

STOT - single exposure May cause drowsiness or dizziness.

Narcotic effects Narcotic effects.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Toluene (108-88-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No.	Rat, male, female	Oral		91 days	NOAEL: 625 mg/kg
440/2008, Annex, B.26					
OECD Test No. 453:	Rat, male, female	Inhalation, vapor			NOAEL: 1.131 mg/l
Combined Chronic					
Toxicity/Carcinogenicity					
Studies					

Aspiration hazard May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Crustacea
Heptane	-	LC50: =375.0mg/L (96h, Cichlid)	EC50: >10mg/L (24h, Daphnia
-			magna)
Kaolin	IC 50 (72h) > 1000 mg/l	LC 50 (96h) > 1000 mg/l	EC 50 (48h) > 1000 mg/l (Daphnia
			magna)
Cyclohexane	EC50 72 h > 9.3 mg/L	LC50: 23.03 - 42.07mg/L (96h,	EC50: >0.9 mg/L (24h, Daphnia
,	(Pseudokirchnerella subcapitata)	Pimephales promelas) LC50: 48.87	magna)
		- 68.76mg/L (96h, Poecilia	

New Zealand Page 9 / 13

GILTGRIP 777 Revision Number 1.01 Revision date 29-Sep-2024 Supersedes date 10-May-2021

		reticulata) LC50: 3.96 - 5.18mg/L (96h, Pimephales promelas) LC50: 24.99 - 44.69mg/L (96h, Lepomis macrochirus)	
Octane	-	-	EC50: =0.38mg/L (48h, Daphnia magna)
Toluene	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)

Terrestrial ecotoxicityThere is no data for this product.

Persistence and degradability No information available.

Bioaccumulative potential Bioaccumulation Component Information

Chemical name	Partition coefficient		
Heptane	4.66		
Cyclohexane	3.44		
Octane	5.18		
Toluene	2.73		

Mobility in soil
Mobility

No information available.

Other adverse effects

No information available.

Disposal methods

Waste from residues/unused products

Dispose of product in packaging in a way that is consistent with the EPA Consolidation 30 April 2021 of the Hazardous Substances (Disposal) Notice 2017 and the Act. Treat the substance using a method that changes the characteristics or composition of the substance so that the substance is no longer a hazardous substance; or export the substance from New Zealand as waste. Flammable substances - may not be disposed of into or onto a landfill or sewage facility.

They may only be burnt in certain situations.

Flammable gases, liquids and solids may only be discharged into the environment or landfill as waste if the substance will not at any time come into contact with any explosives, oxidising gases, liquids or solids or organic peroxides; and there will be no ignition source in the vicinity of the disposal site at any time and if the substance were to ignite, no person, or place where a person may legally be, would be exposed to an unsafe level of heat radiation. Substances which are hazardous to human health or corrosive to metals - may be discharged into the environment if a tolerable exposure limit has been set for the substance (or a component of that substance); and the discharge does not, after reasonable mixing, result in the concentration of the substance in an environmental medium exceeding the tolerable exposure limit. If there is no tolerable exposure limit for the substance, then it may only be discharged into the environment if the substance is very rapidly converted to substances that are not hazardous substances. Environmentally hazardous substances - if the substance, or if it contains a component that is hazardous to the aquatic environment or bioaccumulative and not rapidly degradable, then any component that is bioaccumulative and not rapidly degradable must be removed. The product may only be discharged into the environment if an environmental exposure limit has been set for the substance (or a component of the

New Zealand Page 10 / 13

GILTGRIP 777 Revision date 29-Sep-2024
Revision Number 1.01 Supersedes date 10-May-2021

substance); and the discharge does not, after reasonable mixing, result in the concentration of the substance in an environmental medium exceeding the environmental exposure limit.

Contaminated packaging

For packages that have been in direct contact with hazardous substances, the person must ensure that the package is rendered incapable of containing any substance. It must be disposed of in a manner that is consistent with the requirements for disposal of the substance that it contained, taking into account the material the package is manufactured from. Packages may only be reused or recycled if:

- the substance has a physical hazard other than corrosive to metal, and has been treated to remove any residual contents of the hazardous substance;
- or for substances that have a health or environmental hazard, or corrosive to metal, the contents of the residue in the package are below the threshold for the substance to be classified as hazardous in the Hazardous Substances (Hazard Classification) Notice 2020.

Section 14: Transport information

IATA

UN number or ID number
UN proper shipping name
Adhesives
Transport hazard class(es)

Backing group

Packing group II Special Provisions A3

Description UN1133, Adhesives, 3, II

IMDG

UN number or ID number
UN 1133
UN proper shipping name
Transport hazard class(es)
Packing group
UN1133
Adhesives
3
II

EmS-No. F-E, S-D

Marine pollutant P

Description UN1133, Adhesives, 3, II, (-15°C c.c.), Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

ADR

UN number or ID number UN1133 UN proper shipping name Adhesives

Transport hazard class(es) 3
Labels 3
Packing group |

Description UN1133, Adhesives, 3, II, (D/E), Environmentally Hazardous

Environmental hazardsYesLimited quantity (LQ)5 LSpecial Provisions640DClassification codeF1Tunnel restriction code(D/E)

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EPA New Zealand HSNO approval HSR002662 - Surface Coatings and Colourants (Flammable) **code or group standard**

New Zealand Page 11 / 13

GILTGRIP 777 Revision Number 1.01 **Revision Number** 1.01 **Revision Number** 1.01 **Revision Number** 1.01

National regulations

Any applicable tolerable exposure limits and environmental exposure limits according to the EPA Controls for Hazardous Substances are listed below

Chemical name	Tolerable Exposure	Tolerable Exposure	Tolerable Exposure	Environmental
	Limit (TEL) Air	Limit (TEL) Water	Limit (TEL) Surface	Exposure Limits (EEL)
Toluene 108-88-3	400 μg/m³	0.8 mg/L	-	330 µg/L (Water)

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information

Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information

Controlled substance licenses are required to possess certain explosives, vertebrate toxic agents and fumigants. See Part 7 of the Health and Safety at Work Regulation 2017 for more information

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: Other information

Prepared By Product Stewardship and Regulatory Affairs

Revision date 29-Sep-2024

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Sk* Skin designation

** Skar Skin designation

** Sensitizers

C Carcinogen

New Zealand Page 12 / 13

GILTGRIP 777
Revision Number 1.01

Revision date 29-Sep-2024 Supersedes date 10-May-2021

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

New Zealand Page 13 / 13