

# **Identification of Substance & Company**

#### **Product**

**Product name** Roberts 6037

**Product code** NA

**HSNO** approval HSR002662,

Approval description Surface Coatings and Colourants (Flammable) Group Standard 2020

**UN** number

**Proper Shipping Name** ADHESIVE containing flammable liquid

**DG class** Ш **Packaging group** Hazchem code 3YE

Uses Adhesive suitable for all weather outdoor use.

**Company Details** 

**DGL Bondlast** Company **Address** 24-28 Lady Ruby Drive,

East Tamaki,

Auckland 2013, New Zealand +64 (9) 267 2772

Telephone **Emergency Telephone Number: 0800-764 766** 

### Hazard Identification

# **Approval**

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002662, Surface Coatings and Colourants (Flammable) Group Standard 2020). The substance has been classified as hazardous according to the criteria in the Hazardous substances (Hazard Classification) Notice 2020.

### **GHS 7 Classes**

# **Hazard Statements**

Flammable liquid category 2 Skin irritant category 2

STOT\* single exposure category 3

STOT\* repeated exposure category 1 Chronic aquatic category 2

H225 - Highly flammable liquid and vapour. H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

H372 - Causes damage to organs through prolonged or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

\*STOT - System Target Organ Toxicity

### **SYMBOLS**

# **DANGER**







### Other Classifications

There are no other classifications that are known to apply.



#### **Precautionary Statements**

**Prevention** P103 - Read label before use.

P210 - Keep away from ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe vapours.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/eye/face protection.

**Response** P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P332+P313 - If skin irritation occurs: Get medical advice/ attention. P362 - Take off contaminated clothing and wash before re-use.

P304+P340 - IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.

P314 - Get medical advice/attention if you feel unwell. P403+P235 - Store in a well-ventilated place. Keep cool.

P233 - Keep container tightly closed.

P405 - Store locked up.

**Disposal** P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.

# 3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
hydrocarbon solvent	proprietary	0-50%
heptane	142-82-5	0-50%
Naphtha (petroleum), hydrotreated light	64742-49-0	0-50%
hexane	110-54-3	0-5%

This is a commercial product whose exact ratio of components may vary slightly. Trace quantities of impurities are also likely.

# 4. First Aid

# **General Information**

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been harmed or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service).

Recommended first aid

Ready access to running water is recommended. Accessible eyewash is recommended.

facilities Exposure

Storage

Swallowed IF SWALLOWED: Call a POISON CENTRE or doctor/physician if you feel unwell. Rinse

mouth. Do NOT induce vomiting. Give a glass of water to drink.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical

advice/ attention. Take off contaminated clothing and wash before re-use.

**Inhaled**Generally, inhalation of fumes/vapours/dusts is unlikely to result in adverse health effects.

If coughing, dizziness or shortness of breath is experienced, remove the patient to fresh air immediately. If patient is unconscious, place in the recovery position (on the side) for

transport and contact a doctor.

# **Advice to Doctor**

Treat symptomatically



# 5. Firefighting Measures

Fire and explosion hazards: Vapours may form an explosive mixture in air which can be ignited by many sources such

as pilot lights, open flames, electrical motors, switches and static electricity.

**Suitable extinguishing** Carbon dioxide, extinguishing powder, foam.

substances:

Unsuitable extinguishing

substances:

Unknown.

Products of combustion: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water.

May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying

spaces, forming potentially explosive mixtures.

Protective equipment: Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat and

eye protection.

Hazchem code:

3YE

#### 6. Accidental Release Measures

Containment If greater than 1000L is stored, secondary containment and emergency plans to manage

any potential spills must be in place. In all cases design storage to prevent discharge to

storm water.

**Emergency procedures** In the event of spillage alert the fire brigade to location and give brief description of hazard.

Stop the source of the leak, if safe to do so. Shut off all possible sources of ignition. Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain using sand, earth or vermiculite. Do not use sawdust. Prevent by whatever means possible any spillage from entering drains, sewers, or water

courses. (If this occurs contact your regional council immediately).

clean-up of spills, as they may create fire or environmental hazard. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or

waterways has occurred advise local emergency services.

**Disposal** Mop up and collect recoverable material into labelled containers for recycling or salvage.

Recycle containers wherever possible. This material may be suitable for approved landfill.

Dispose of only in accord with all regulations.

Precautions Wear protective equipment to prevent skin and eye contamination and the inhalation of

vapours. Work up wind or increase ventilation.

### 7. Storage & Handling

Storage Avoid storage of harmful substances with food. Store out of reach of children. Containers

should be kept closed in order to minimise contamination. Keep from extreme heat and open flames. Avoid contact with incompatible substances as listed in Section 10. Location compliance certificates must be available if storing >100 L (closed containers greater than 5 L), 250 L (closed containers up to and including 5 L), 50 L (open containers). Containers (and outer packaging) must bear the prescribed labelling, including the Hazchem code, UN

number, flammability warning and name of contents.

**Handling** Keep exposure to a minimum, and minimise the quantities kept in work areas. Use only in

well ventilated areas. Open containers cautiously as contents may be under pressure. See section 8 with regard to personal protective equipment requirements. Avoid skin and eye

contact and inhalation of vapour, mist or aerosols.

### 8. Exposure Controls / Personal Protective Equipment

# **Workplace Exposure Standards**

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

NZ Workplace	
<b>Exposure Stds</b>	

ingredient
hydrocarbon solvent

Ingradiant

heptane n-hexane

#### **WES-TWA**

100ppm, 525mg/m2 400ppm, 1640mg/m<sup>3</sup> 20ppm, 72mg/m<sup>3</sup>

# WES-STEL

data unavailable 500ppm, 2050mg/m³ data unavailable



#### **Engineering Controls**

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

#### **Personal Protective Equipment**

General Personal Protective Equipment (PPE) should not be used as the primary means of

exposure protection, except in the event of an accident or emergency situation or where

all other means of protection have proven to inadequate.

Clean PPE after use or dispose of as appropriate. Store PPE for re-use in a clean place. Regular training on the correct use of PPE should be provided. In particular the correct fitting and use of respirators and where applicable the cleaning of respirators should be

undertaken.

**Eyes** Protective eyewear is not normally necessary when using this product. However, it always

prudent to use protective eyewear if splashes are likely.

Avoid any skin contact. Wear overalls, rubber boots and impervious gloves. Nitrile gloves are recommended. Protective gloves or suitably resistant material must comply with AS

2161. Replace frequently. Gloves should be checked for tears or holes before use. Protective clothing must comply with AS 2919, AS3765.1 or AS3765.2. PVC or rubber boots must comply with AS/NZS 2210.2 and selected and maintained in accordance with AS/NS2210.1. Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or smoking.

Respiratory

Skin



A respirator when airborne concentrations approach the WES (section 8). Respirators must have filters appropriate to the duty and comply with AS/NZS1716 and selected, used and maintained in accordance with AS/NS 1715. Use a respirator with an organic vapour cartridge. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order. Fit testing and clear guidelines and training for use and maintenance of PPE are necessary.

# **WES Additional Information**

Not applicable

# 9. Physical & Chemical Properties

**Appearance** opaque beige paste Odour hydrocarbon odour

**Odour Threshold** no data Hq no data Freezing/melting point no data **Boiling Point** >40°C

**Flashpoint** <-20°C (closed cup)

Flammability flammable

Upper & lower flammable limits no LEL or UEL for the mixture

Vapour pressure no data Vapour density no data Specific gravity/density ~1.0

Solubility miscible in water

Partition coefficient no data Auto-ignition temperature no data Decomposition temperature no data Viscosity no data Particle Characteristics no data

# 10. Stability & Reactivity

Stability Conditions to be avoided

Flammable substance. Keep away from sources of ignition at all times. Containers should

be kept closed in order to avoid contamination.

Incompatible groups Strong oxidisers. **Substance Specific** none known

Incompatibility Hazardous decomposition

products

Thermal decomposition products include oxides of carbon.

**Hazardous reactions** 

none known



# 11. Toxicological Information

#### Summary

IF SWALLOWED: may cause gastrointestinal irritation resulting in nausea, pain and vomiting. May have effects on the central nervous system and aspiration into the lungs is possible.

IF IN EYES: may cause transient eye irritation.

IF ON SKIN: may cause irritation. Prolonged or repeated exposure may result in dryness and cracking and non allergic dermatitis.

IF INHALED: vapours may cause dizziness and drowsiness. Symptoms of overexposure may include fatigue, headaches, shortness of breath and nausea. Very high concentrations may cause loss of coordination, impaired judgement, unconsciousness and death.

CHRONIC TOXICITY: prolonged and repeated exposure may affect the central and peripheral nervous system.

#### **Supporting Data**

Acute Oral Using LD50's for ingredients, the Acute Toxicity Estimate (ATE) (oral) for the mixture is

>2,000 mg/kg. Data considered includes: hydrocarbon solvent >15000mg/kg (rat), heptane aspiration hazard, Naphtha (petroleum), hydrotreated light 5000mg/kg (rat),

hexane 25000mg/kg (rat).

**Aspiration** This mixture is not considered an aspiration hazard since it is a paste. The ingredients may

be considered an aspiration hazard.

>2,000 mg/kg. Data considered includes: hydrocarbon solvent >3160 mg/kg (rabbit),

Naphtha (petroleum), hydrotreated light >5000mg/kg (rabbit).

Inhaled Using LD<sub>50</sub>'s for ingredients, the Acute Toxicity Estimate (ATE) (inhalation) for the mixture

is >5mg/L/4h. Data considered includes: hydrocarbon solvent >12mg/L (rat), Naphtha

(petroleum), hydrotreated light >4.951mg/L (rat), hexane 48000ppm/4H (rat).

Eye The mixture is not considered to be an eye irritant.

**Skin** The mixture is considered to be a skin irritant, because some of the ingredients present

are considered skin irritants in more concentrated form.

**Chronic** Sensitisation No ingredient present at concentrations > 0.1% is considered a sensitizer.

MutagenicityNo ingredient present at concentrations > 0.1% is considered a mutagen.CarcinogenicityNo ingredient present at concentrations > 0.1% is considered a carcinogen.

Reproductive / No ingredient present at concentrations > 0.1% is considered a reproductive or

**Developmental** developmental toxicant or have any effects on or via lactation.

The mixture is considered to be a known or presumed target organ toxicant, because at least one of the ingredients present in greater than 1% is known or presumed to be a target

organ toxicant. Heptane may affect the central nervous system. Vapours may cause dizziness and drowsiness. Hexane is known to affect the peripheral nervous system.

Aggravation of None known.

existing conditions

Systemic

### 12. Ecological Data

#### Summary

This mixture is considered toxic towards aquatic organisms with long lasting effects. In all cases prevent run-off to drains, sewers and waterways.

#### **Supporting Data**

**Aquatic** Using EC<sub>50</sub>'s for ingredients, the calculated EC<sub>50</sub> for the mixture is between 1 and 10 mg/L.

Data considered includes:

hydrocarbon solvent 2200mg/L (96hr, fish), 2.6 mg/L (96hr, Crustacea),

heptane 1.5 mg/l 948hr, Daphnia magna),

Naphtha (petroleum), hydrotreated light EL50 > 1000 mg/l (algae) (green algae / 72 h), 22-46 mg/l (daphnia) (daphnia magna / 48 h), LL50 10-30 mg/l (fish) (Oncorhynchus

mykiss / 96 h), NOELR <1 mg/l (algae) (green algae /72 h),

hexane 2.50mg/L (96hr, Fathead minnow), 3.9mg/L )48hr, Daphnia magna)

**Bioaccumulation** Some of the hydrocarbon ingredients are considered bioaccumulative.

**Degradability** No data

Soil No evidence of soil toxicity.

Terrestrial vertebrate See acute toxicity.

**Terrestrial invertebrate**This mixture is not classified the mixture as ecotoxic to terrestrial invertebrates.

**Biocidal** no data



### 13. Disposal Considerations

Restrictions There are no product-specific restrictions, however, local council and resource consent

conditions may apply, including requirements of trade waste consents.

Disposal method

Disposal of this product must comply with the Hazardous Substances (Disposal) Notice

2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore

rendered non-hazardous before discharge to the environment.

Contaminated packaging Disposal of contaminated packaging must comply with the Hazardous Substances

(Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible

reuse or recycle packaging.

### 14. Transport Information

## Land Transport Rule: Dangerous Goods 2005 - NZS 5433:2007

Transport according to NZS 5433 (Transport of Hazardous Substances on Land). Considered a dangerous good for transport.

**UN number:** 1193 **Proper shipping name:** ADHESIVE containing flammable

liquid II IIaIIIIIabie

Class(es) 3
Precautions: Ecotoxic.

Packing group: Hazchem code:

3YE

# 15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002662, Surface Coatings and Colourants (Flammable) Group Standard 2020. All ingredients appear on the New Zealand Inventory of Chemicals NZIoC.

### **Specific Controls**

Key workplace requirements are:

SDS To be available within 10 minutes in workplaces storing any quantity.

Inventory An inventory of all hazardous substances must be prepared and maintained.

Packaging All hazardous substances should be appropriately packaged including substances

that have been decanted, transferred or manufactured for own use or have been

supplied

Labelling Must comply with the Hazardous Substances (Labelling) Notice 2017.

Emergency plan Required if > 1000L is stored.

Certified handler Not required.
Tracking Not required.

Bunding & secondary containment Required if > 1000L is stored. Signage Required if > 250 L is stored.

Location compliance certificate Required if > 100 L (closed containers greater than 5 L), 250 L (closed containers

up to and including 5 L), 50 L (open containers) is stored.

Flammable zone Must be established if > 100 L (closed containers), 25 L (decanting), 5 L (open

occasionally), 1 L (open containers in continuous use) is stored.

Fire extinguisher If > 250 L present.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

### Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.



### 16. Other Information

**Abbreviations** 

Approval Code Approval HSR002662, Surface Coatings and Colourants (Flammable) Group Standard

2020 Controls, EPA. www.epa.govt.nz

CAS Number Unique Chemical Abstracts Service Registry Number

ECotoxic Concentration 50% - concentration in water which is fatal to 50% of a test

population (e.g. daphnia, fish species)

EPA Environmental Protection Authority (New Zealand)

Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised

edition, 2017, published by the United Nations.

HAZCHEM Code Emergency action code of numbers and letters that provide information to emergency

services, especially fire fighters

HSNO Hazardous Substances and New Organisms (Act and Regulations)

International Agency for Research on Cancer

**LEL** Lower Explosive Limit

**LD**<sub>50</sub> Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).

**LC**<sub>50</sub> Lethal Concentration 50% − concentration in air which is fatal to 50% of a test population

(usually rats)

NZIoC New Zealand Inventory of Chemicals

STEL Short Term Exposure Limit - The maximum airborne concentration of a chemical or

biological agent to which a worker may be exposed in any 15 minute period, provided the

TWA is not exceeded

**STOT RE**System Target Organ Toxicity – Repeated Exposure
STOT SE
System Target Organ Toxicity – Single Exposure

TWA Time Weighted Average – generally referred to WES averaged over typical work day

(usually 8 hours)

UELUpper Explosive LimitUN NumberUnited Nations Number

WES Workplace Exposure Standard - The airborne concentration of a biological or chemical

agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring using

procedures that gather air samples in the worker's breathing zone.

References

Unless otherwise stated comes from the EPA HSNO chemical classification information

database (CCID).

Controls EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances)

Regulations 2017, www.legislation.govt.nz

WES The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available

on their web site – www.worksafe.govt.nz.

Other References: Suppliers SDS

Review

Date Reason for review
February 2023 Not applicable - New SDS

### **Disclaimer**

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely GHS 7 classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 21 1040951.

