


# Customer Services CHC: 03 379 7067 or AKL: 09 443 7067 Email: help@giltedge.co.nz

Technical & Sales Assistance Email: help@giltedge.co.nz www.giltedge.co.nz

# **PRODUCT DATA SHEET**

### 63006.5mm - Hybrid Box Edge Trim



Floating Floor Hybrid Box Edging are used to finish off the edges of your new timber floor where it joins other floor coverings like carpet, vinyl, ceramic tiles, or timber. They are also designed to cover expansion gaps in doorways and within larger floor areas.

#### **Product Attributes**

63006.5mm - Hybrid Box Edge Trim is an aluminium, colour anodised, edge capping for floating floors edging. Suitable for interior and exterior use and suitable for 5mm to 6.5mm floor coverings.

Material: Aluminium Colours: Satin Silver/ Matt Black/ Champagne Anodised Length: 2.5mtr

# **Specification**

Manufacturer: Gilt Edge Industries 110 Antigua Street, Addington Christchurch 8240

P O Box 7515 Sydenham Phone: 0800 445 833 Fax: 0800 103 649

Email: help@giltedge.co.nz

Reference Code: 6300S6.5mm Satin Silver

6300B6.5mm Matt Black 6300C6.5mm Champagne

#### Installation

The Floating Floor Hybrid Box Edge is the most widely used trim and is ideal for areas where flooring is joining carpet, ceramic tiles (at the same height), window frames, sliding door tracks and walls. This trim should be adhered to the floor with a permanent construction adhesive. Box Edging, skirting or scotia over expansion gaps, should be fasten to the wall only, never to the flooring itself. Fill the expansion gaps with an elastic filler in places where profiles or skirtings cannot be placed. Is suitable for use in both domestic and commercial applications. The timber or laminate is designed to sit just under the outside lip of the trim, leaving room for expansion inside the channel.

## Maintenance

A regular scheduled maintenance programme prevents build-up of dirt and grease, which will reduce properties of and detract from the overall appearance of the product. Brush down the profiles using a soft bristled brush.

With clean warm water, apply a small amount of a soap-less detergent to a wet green scotch pad and gently clean the surface of the profile along it's width with fresh, clean water and dry with a dry lint free cloth.