



Customer Services CHC : 03 379 7067 or AKL: 09 443 7067 Email: help@giltedge.co.nz Technical & Sales Assistance Email: sales@giltedge.co.nz www.giltedge.co.nz

Ramp Edge

Performance Characteristics

- Long, flat, inclined ramps of different widths and thicknesses
- Designed to smooth the transition under different thickness floorcoverings
- Slope ratios meet standards contained in AS1228.1:2009 Design for Access and Mobility

Construction

- Milled from High Moisture Resistant MDF (HMR MDF)
- Made from 100% FSC certified trees (Cert. No. SCS-FM/COC-005851)

Installation

- Ensure the sub-floor is clean, dry, sound and free of contamination
- Assess the floorcovering materials and ramping height required
- Select your RampEdge ramp to achieve the ramping required
- Measure and cut your RampEdge ramp to fit
- Affix firmly into place using adhesive, screws or nails ass appropriate

Physical Data

SKU	Length	Width	Thick Edge	Thin Edge	Packs	Pack Weight
	mm	mm	mm	mm	#	kg
Ramp5	1,200	100	5	1	10	2.3
Ramp8	1,200	112	8	1	10	4.0
Ramp12	1,200	145	12	1	10	7.8
Ramp12Wide	1,200	300	12	1	10	16.2

Version 1 July 2019



Customer Services CHC : 03 379 7067 or AKL: 09 443 7067 Email: help@giltedge.co.nz Technical & Sales Assistance Email: sales@giltedge.co.nz www.giltedge.co.nz

HIGH MOISTURE RESISTANT MDF

