



Gilt Edge Industries Ltd®

TECHNICAL DATA SHEET

Customer Services
CHC : 03 379 7067 or AKL: 09 443 7067
Email: help@giltedge.co.nz

Technical & Sales Assistance
Email: help@giltedge.co.nz
www.giltedge.co.nz

ROLL STRIPPER RO-1

Compact ride-on stripper machine for professional removal of all extremely bonded floor coverings.



SPECIAL FEATURES:

- For medium and large areas in commercial property
- Maximum efficiency by the striking mechanism
- Stepless working angle for optimal use on different floor coverings and surfaces
- Effortless work by comfortable joystick control
- Quiet operation by industrial electric motors
- Very manoeuvrable and compact
- Variable additional weights

AREAS OF APPLICATION:

- Removal of parquet
- Removal of ceramic tiles
- Removal of elastic floor coverings
- Removal of textile floor coverings

TECHNICAL SPECIFICATIONS:

Drive engines left/right: each 1,5 kW, 230 volts

Torque: 654 Nm

Adjustable speed (joystick operation) up to 37 m / min

Stroke engine: 1,1 kW, 230 volts

Blow count: 2000 beats per minute (bpm)

Lifting motor: 8600 N nominal force

Working angle infinitely adjustable up to 40°

Working width: 120 / 250 / 300 / 350 mm

Dimensions: 1050 x 600 x 1100 mm

Weight: 528 kg, modular construction (removable additional weights)