Giltgrip Simlay Plus Double Bond Underlay BPIR Declaration

Version: V1.01112023

Designated building product: Class 1

Declaration

Autodec Supplies Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Giltgrip Simlay Plus Double Bond Underlay
Identifier	RULSIMPLUS

Description

Giltgrip Simlay Plus is a premium grade SBR rubber double bond underlay for use in heavy contract commercial environments and high traffic areas including healthcare, aged care, hospitality, offices, apartments.

Made from materials:

- Backing Material: Topside Textron re-inforced paper.
- Downside Hessian

Dimension:

Roll Width: 1800mm.
Roll Length: 10mtr.
Roll Weight: 30kg.
Thickness: 4.7mm

Scope of use

Giltgrip Simlay Plus Double Bond Underlay is a premium grade SBR rubber double bond underlay for use in heavy contract commercial environments and high traffic areas including healthcare, aged care, hospitality, offices, and apartments. It is produced in a continuous sheet with square trimmed edges. Double-stick system

means rapid installation with no rucking or stretching of carpet. Up to 50% increase in carpet life compared with conventional & direct-stick methods. Increases thermal insulation for reduced energy consumption and warmer rooms. Improves Impact Insulation Class Ratings essential in reducing transference of noise. Suitable for all floor types, including heated slabs. Anti-microbial. Recyclable.

Conditions of use

Important to follow GiltEdge 3 Step Total Flooring System Installation

- 1. CONCRETE TREATMENT: Concrete Slab Treated with Protect Crete X200 Densi-Proof (at time of pour) to cure, densify, protect and moisture control.
- 2. SUPPORTAPAD GLUED TO SUBFLOOR: Carpet Adhesive: Giltgrip 22 or Roberts 80or Pressure Sensitive Adhesive: Giltgrip 66 or Polymer 999.
- CARPET TILES GLUED TO SUPPORTAPAD Pressure Sensitive Adhesive: Giltgrip 66 or Polymer 999 Or Carpet Adhesive (If required): Giltgrip 22 or Roberts 80

Contributions to compliance

Building Regulations 1992 - Clause 2B-Durability Giltgrip Simlay Plus Double Bond Underlay, with only normal maintenance, will continue to satisfy the performance requirements of Building Regulations for 10 years or for the life of the installed carpet.

Supporting documentation

The following additional documentation supports the above statements:

Giltgrip Simlay Plus Technical Data Sheet	Versiion January 2022	https://giltedge.co.nz/download/tds-rulrulsim-simlay?wpdmdl=9035&refresh=656bce959b5961701564053
Giltgrip Simlay Plus Acoustic Testing Result	Version July 2020	https://giltedge.co.nz/download/simlay-p lus-acoustic-testing-data?wpdmdl=1069 5&refresh=656bce95d57141701564053
Giltgrip Simlay Plus Emission Test	Version June 2008	https://giltedge.co.nz/download/voc-rulru lsim-simlay?wpdmdl=9036&refresh=656 bce95b854a1701564053

For further information supporting Giltgrip Simlay Plus Double Bond Underlay claims refer to our website.

Contact details

Manufacture location	New Zealand
Legal and trading name of manufacturer	Autodec Supplies Limited
Manufacturer address for service	73 Cryers Road East Tamaki
Manufacturer website	
Manufacturer email	sales@autodec.co.nz
Manufacturer phone number	09 272 2244
Manufacturer NZBN	9429040470405

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Giltgrip Simlay Plus Double Bond Underlay is not subject to a warning on ban under <u>s26 of the Building Act</u>.

AUTODEC SUPPLIES LIMITED

73 Cryers Road East Tamaki New Zealand 09 272 2244 |

BPIR Ready selections

Category: Other (custom)