



Gilt Edge Industries Ltd*

TECHNICAL DATA SHEET

Customer Services
CHC : 03 379 7067 or AKL: 09 443 7067
Email: help@giltedge.co.nz

Technical & Sales Assistance
Email: sales@giltedge.co.nz
www.giltedge.co.nz

5157

Golden Grip Plateau Heat Resistant Tape

PERFORMANCE CHARACTERISTICS

- **Extremely low smoke and odour**
 - less distress for the installer, building occupants and pets
 - less chance of smoke alarms activating
- **Backed with a SUPER-RELEASE silicon coating**
 - for easier release over foam underlays
 - making SureSeam® quicker and easier to handle
- **Heat-resistant hotmelt formulation**
 - older style carpet tapes can re-open in direct summer heat
 - Sureseam® is formulated with 'heat resistance' to prevent seams re-opening
- **Wide centre-bead puts 22% more hotmelt on the seam**
 - seam centre is held down to reduce visible peaking
- **Hotmelt and fibreglass are 'pressure bonded' together**
 - the fibreglass and hotmelt are pressure bonded together in manufacture
 - this pressure bond makes SureSeam® a stronger joining tape
- **9 picks/inch of double stranded fibreglass**
 - greater seam strength is achieved with more fibreglass
 - fibreglass strands are laid straight, without warp, or bow. This eliminates tension release on stretching.

CONSTRUCTION

- 90mm flat Kraft backing paper
- SUPER-RELEASE silicone coating on paper reverse side
- 65mm fibreglass and cotton knitted scrim
- 9 ppi (picks per inch) double stranded fibreglass
- Straight laid fibreglass strands
- 65mm hotmelt coating with an 18mm wide centre bead

INSTALLATION

- Install as per Australian Standards
- Recommendations for use
 - in domestic and commercial installations, where there is light, medium and heavy foot traffic
 - To seam tufted and woven carpets with both tight and open weave backings
 - With Jute and ActionBac carpets, as well as many synthetic backings* (*if in doubt, conduct a seaming test on an offcut of carpet before seaming.)

PHYSICAL DATA

Packaging: 100m rolls – **Coverage:** 100m of carpet seams – **Weight:** 4.3kg Approx. per roll

