

# Technical Data Sheet

## MULTIPRIME



architectural +  
structural  
adhesives

### DESCRIPTION

**Multiprime** is a synthetic latex based liquid which can be used for priming a variety of substrates prior to the use of **ASA** adhesives and **ASA** water based waterproofing membranes. **Multiprime** will eliminate dust and reduce porosity of plasterboard, fibrous cement sheeting, cement render, porous concrete and timber floors.



### FEATURES & BENEFITS

- Reduces porosity
- Makes adhesive application easy
- Stops premature drying of adhesives
- Eliminates dust
- Expands open time

### RECOMMENDED FOR

- Porous concrete
- Cement render
- Blockwork
- Brickwork
- Hebel blocks
- Sand/cement screeds
- Fibrous cement sheeting
- Plasterboard
- Timber
- Particleboard

### SURFACE PREPARATION

Surfaces must be firm, clean, dry, sound and smooth. All grease, oil, wax, curing compound, dust, plaster droppings and paint must be removed prior to the application of **Multiprime**. Building boards, timber and particleboard flooring must be fixed in accordance to the manufacturer's directions. Timber and particleboard flooring must be sanded prior to application of **Multiprime**. Cement render must be allowed to cure for at least 7 days and concrete for at least 28 days.

### APPLICATION

Apply **Multiprime** onto the correctly prepared surface using a brush, roller or sponge. Allow to dry for at least 30 minutes prior to the application of adhesive or waterproofing membrane.

### CLEAN UP

**Multiprime** can be cleaned up using warm water and detergent prior to the product drying.

### PACKAGING

20 litre, 5 litre and 1 litre plastic jerry cans.

### COVERAGE

Approximately 8m<sup>2</sup> per litre depending on porosity of substrate.

### SAFETY PRECAUTIONS

This product is non-toxic and has no known harmful effects. It is advisable to wear gloves and use good occupational health and safety practices to avoid personal contact. For more detailed information refer to product MSDS.

### SHELF LIFE

Unopened containers can be stored for up to 12 months in a cool, dry and weatherproof environment

### LIMITATIONS

- Do not use on non-porous surfaces such as existing tiles, waterproofing membranes or steel trowel finished floors
- Only suitable on porous surfaces
- Do not apply the product in extreme temperatures of below 5°C and above 30°C

**DISCLAIMER:** *It is the users responsibility to check and read the latest updated Data Sheet and related information before using the product. Users should also check and perform their own tests when assessing the suitability of a product for a particular application under certain conditions.*

# Technical Data Sheet

## MULTIPRIME



architectural +  
structural  
adhesives

PHYSICAL PROPERTIES	
Appearance:	Clear/tinted thin liquid
Mixing ratio:	No mixing
pH:	8 - 9
Specific Gravity:	1.02g/cm

**TECHNICAL SERVICES TOLL FREE NUMBER**  
**1800 813 890 Australia**  
**0508 222 272 New Zealand (land lines only)**  
or visit [www.asaltd.com.au](http://www.asaltd.com.au)  
a member of the Bostik group of companies



### GUARANTEE

ASA guarantees this product for 10 years provided application is in accordance with manufacturer's directions and the Australian Standards for Tiling Practice. ASA's liability is limited to the cost of replacing effected ASA product only. ASA reserves the right to inspect. Contact ASA for full guarantee terms.

NSW HEAD OFFICE	VIC	QLD	SA	WA	NZ
Ph: (02) 9725 4666 Fax: (02) 9725 4427	Ph: (03) 9261 4733 Fax: (03) 9261 4744	Ph: (07) 3260 2422 Fax: (07) 3260 2411	Ph: (08) 8244 2853 Fax: (08) 8244 0522	Ph: (08) 9314 5200 Fax: (08) 9337 4377	Ph: +64 9270 3168 Fax: +64 9270 6170