Tuf as Nails

Original formula

DESCRIPTION:

A fast drying, solvent based panel mastic adhesive. Bonds quickly on contact, adds rigidity and stiffness, eliminates movement.

RECOMMENDED USES:

- Bonding of polystyrene panels (original formula only)
- Bonding all common building panel materials
- Steel, aluminium and other materials to hardboard, plasterboard. cement sheet, timber or concrete
- Excellent for bonding solvent sensitive surfaces such as mirror
- Tuf As Nails Original Formula is the adhesive of choice for acrylic shower linings

FEATURES AND BENEFITS:

- Excellent gunnability, even at low temperatures
- Very low slump on vertical & overhead application
- Suitable for use on LOSP (not solvent wet) framing
- Very good wet grab (early strength)

APPLICATION:

Bostik Tuf as Nails Original may be used as the sole bonding agent or in conjunction with conventional mechanical fasteners. Can be used one way, wet bond, or two way - press the bond surface together, separate, then re-bond for faster strength build-up.

For heavy panels/high loads, use together with mechanical fasteners.

PROPERTIES:

Viscosity:	Medium to heavy non slump paste
Type:	Synthetic rubber / resin / filler
Flammability:	Class 3, HIGHLY FLAMMABLE
Specification:	Tuf As Nails Original Meets AS 2329 Mastic Adhesives for fixing wallboards
Cleaner:	Bostik No. 1 solvent in polystyrene applications, mineral turps in others while adhesive is wet. Dried Tuf as Nails is best removed by scraping, cutting or sanding
COVERAGE:	22-24 metres at 5mm bead per 375ml cartridge, 38-40 metres per 600ml sausage
PACKAGING:	375ml cartridges



BOSTIK CODES: Original 022468