

# BUTYLSEAL TAPE

## FLEXIBLE WATERPROOFING TAPE

### Characteristics:

- Butylseal Tape is a grey butyl rubber tape with excellent elongation properties and a degree of memory.
- Butylseal does not shrink and is permanently flexible.
- It is non-soluble and waterproof.
- Butylseal can be painted and plastered over.
- Designed for use on timber, plywood, fibre cement, concrete, masonry block, gib board, most metals, steel and plastic roofing, plastic sheet wall linings, glass and fibreglass.
- Recommended for use within waterproofing and floor levelling systems.



### Preparation:

- Surfaces must be free of oil, grease, wax, curing compounds, dust, old adhesives and any other contaminants that may inhibit bonding.
- Surfaces should be dry and not subject to excessive movement.
- Ensure all concrete surfaces have had sufficient cure time, and that all other surfaces and products are fixed in accordance to the manufacturer's specifications and relevant standards.
- It is recommended that surfaces are primed with Universal Primer prior to application.

### Application:

- Place Butyl tape in place, ensuring any joints are overlapped a minimum of 50mm.
- Apply pressure to tape to ensure it is well bonded to substrate.
- Apply pressure to joints with a roller to join mould laps together and confirm tape adhesion.

### Cleanup:

- Scrape excess Butylseal Tape off substrate and dispose.
- Clean tools and surfaces if necessary with a solvent, ensuring correct protective equipment is used.

### Packaging/Storage:

- Butylseal Tape has an indefinite life when stored correctly.
- Store in a dry area, above ground and out of direct sunlight.
- Do not store in areas above 40°C.
- Butylseal Tape single-sided (woven backing) is available in 80mm, 150mm, 500mm widths, in 15m rolls.
- Butylseal Strip Tape is available in 25mm x 37m rolls.
- Butylseal Manhole Sealant is available in 15mm x 3.81m rolls.
- Butylseal Corners are available for both internal and external joints.

Part of the

**Flexi-SEAL**  
Licensed waterproofing system

### Attributes:

- Butylseal Tape is a smooth grey rubber mastic tape.
- Butylseal Tape will deform under compression.
- Butylseal may be applied from 0°C to 40°C.
- Butylseal will remain serviceable from -20°C to 80°C.
- Butylseal has up to 400% elongation at break.

### Notes:

A Material Safety Datasheet is available at request.

Disclaimer: The information supplied is to the best of our knowledge true and accurate. The actual application of the product is beyond the manufacturers control. Any failure or damage caused by the incorrect usage of the product is not the responsibility of the manufacturer. The manufacturer insists that all workmanship must be carried out in accordance with AS 3958.1-2007. It is also the responsibility of the end user to ensure that the literature in their possession is the latest issue.



RLA Polymers NZ Ltd  
24 - 28 Lady Ruby Drive  
PO Box Botany 2163  
Auckland 2013  
New Zealand

**S O L U T I O N S   F O R   I N D U S T R Y**

Phone: (09) 267 2772  
Fax: (09) 268 0305  
Email: sales@rlapolymers.co.nz  
Web: www.rlapolymers.co.nz