

INTERTAC + ADHESIVE

PRODUCT DESCRIPTION

Intertac+ Adhesive is a Solvent Free, Low Odour, Low VOC Pressure Sensitive adhesive formulated for installing Interface Glass Bac Carpet Tiles and Loose Lay Vinyl Planks.

SURFACE PREPARATION

To be in accordance with the current Australian Standard "Floor Coverings - 1884-2012 Resilient Sheet & Tiles - Laying & Maintenance Practices" or Australian Standard 2455.2.2007 "Textile Floor Coverings - Installation Practice".

All surfaces to be bonded shall be absorbent, dry, smooth, sound and clean. Subfloors must also be free of wax, grease, paint, previously used adhesive, polish, PVC based membranes and hydrostatic pressure.

All concrete floors should be tested for moisture content in accordance the above Australian Standards prior to the undertaking surface preparation or installation of floorcoverings.

The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C.

It is recommended that highly absorbent concrete subfloors be primed with Roberts R400 floor and wall primer prior to the application of adhesive.

APPLICATION & SPREAD RATE

Intertac+ Adhesive may be applied using different techniques, depending on the installation.

1. For securing Interface Glass Bac Carpet tiles we recommend the use a log nap roller with a pile height of no less than 10mm is recommended.
The use of a long nap roller with a pile height of no less than 10mm can achieve an approx spread rate of 10-14 square metres per litre.
In some cases a higher spread rate on application can be achieved when applied over low absorbent substrates.
Alternatively applying adhesive with a 1.6mm notched "V1" notched trowel will achieve up to 5 square metres per litre.
2. For securing Interface loose lay vinyl planks to a sub floor a 1.6mm "V1" notched trowel is recommended. Coverage up to 5 square meters per litre.

Intertac+ Adhesive is used in dry mode, allow the adhesive to dry and become clear, this will limit the transfer of the adhesive to the back of the carpet tiles therefore enabling them to be relayed or repositioned with a clean backing.

A stronger bond can be achieved by laying the material into the adhesive film just prior to it drying completely, this will cause some transfer onto the back of the material.

CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using R550 Latex/Acrylic Adhesive Remover applied to a damp cloth then rubbed gently over the dried adhesive or alternatively please use AFTEK Handy Wipes.

SHelf LIFE

12 months in unopened containers stored out of direct sunlight.

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 739 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au

STORAGE

Keep in well ventilated areas stored out of direct sunlight.

CONTAINER SIZES

15 litre plastic containers

SAFETY & HANDLING

A Safety Data Sheet is available on request.

FIRST AID

For advice contact a Poison Information Centre (Australia PH: 13 11 26 , New Zealand PH: 0800 764 766) or a doctor at once. A Material Safety Data Sheet is available on request.

Issued: February 2017

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 739 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au