



6037 Synthetic Carpet Adhesive

Product Description

Roberts 6037 Synthetic Carpet Adhesive is an all-weather solvent based (flammable) adhesive specifically formulated for the indoor, or outdoor installation of non-stretch open weave polypropylene or rubber backed synthetic carpets.

Roberts 6037 Synthetic Carpet Adhesive develops high strength quickly, and when cured will withstand unfavourable weather conditions. It will bond securely to cured concrete, timber, asphalt, exterior grade wood and other clean paved surfaces, and is ideal for use around swimming pools, balconies, outdoor recreational areas and other applications which are subject to moisture after fixing.

Surface Preparation

To be in accordance with the Australian Standard 2455.1:1995 "Textile floor covering - installation practice".

All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease & hydrostatic pressure.

All concrete substrate floors should be tested for moisture content, prior to undertaking surface priming or installation of floorcovering.

Application

Rough cut and lay out carpet according to manufacturer's instructions. Spread adhesive with the recommended notched trowel. Allow adhesive to tack up slightly before floorcovering is lowered. Tack-up time will depend upon atmospheric conditions and can be determined by placing a small piece of floorcovering into the adhesive. When the floorcovering is pulled away, strings of adhesive should be apparent. If no tack or holding power has developed, wait five minutes re-checking every few minutes thereafter.

Complete the installation according to floorcovering manufacturer's instructions. Do not allow heavy traffic for 24 hours. All seams must be sealed using Roberts 5216 Carpet Seam Adhesive.

Do not use in rain or if rain is expected during or immediately after laying.

Clean Up

To clean up equipment and adhesive spills, use Roberts 900 Cleaner/Thinner (flammable). Roberts 900 is not recommended for removing adhesive from vinyl, carpet or painted surfaces.

Typical Properties

Appearance Brown

Base Synthetic Rubber

Solids Approx 58%

Viscosity Trowellable Mastic

Shelf Life Up to 1 year in sealed container at 20°C

Flash Point Less than 0°C

Freezability Avoid freezing

Packaging 20, 4 litre

Trowel Size **Smooth backed carpet / Smooth substrate**

1.5 - 2.0mm "V" notched

Coverage up to 4.0m²/litre

Textured backed carpet / Rough substrate

3.0 x 1.6mm "V" notched

Coverage up to 2.0m²/litre

Highly Flammable

Avoid contact with skin and eyes and avoid breathing vapour.

First Aid

If poisoning occurs, contact a Doctor or Poisons Information Centre.

If swallowed, do NOT induce vomiting. Give a glass of water.

Material Safety Data Sheet available upon request.