

35 Fine Patch

Roberts Fine Patch 35 provides a smooth permanent finish, to a variety of substrates, prior to installation floor coverings such as vinyl sheets and tiles. Roberts Fine Patch 35 contains no sand therefore giving the user a true featheredge. Roberts Fine Patch 35 allows the installation of most types of floor covering in as little as 20 minutes over concrete, ceramic and quarry tiles. Use Roberts Fine Patch 35 to smooth ridges, fill in scratches, gouges and joints to provide a true featheredged over concrete, wood, terrazzo, ceramic and quarry tiles.

Sub Floor Preparation

Sub floor must be free of oil, grease, wax, curing compounds, dust, old adhesive and any other contamination, which may inhibit bond. Do not use curing compounds, solvents or acids, etching to prepare the substrate. Sub floors must be dried at a minimum of 10 degrees centigrade.

Note:

Concrete floors must be dry in accordance with A.S.1884-1985 Appendix A- 70% Relative humidity maximum

Mixing

Place a small amount of clean water in a clean pail, and then add a small amount of powder while mixing to achieve the desired consistency. Over watering of Fine Patch 35 will reduce the tensile and bond strength.

Application

Apply the mixed compound to the substrate using a trowel. Can be applied from feather edged to 3mm thickness. Impetrations or minor trowel marks can be removed after 1 hour by gentle sanding. Allow to dry before installing floor coverings wipe any sanded areas with a damp cloth to remove dust prior to installing floor coverings.

Clean up

Clean all equipment with water immediately after use.

Packaging

Roberts Fine Patch 35 10 kg Paper Bags

Storage

Roberts Fine Patch 35 is a cement-based product, which must be stored in a dry area off the ground and out of direct sun light

Coverage

Approximately 8m² @ 1mm thickness per 10 kg bag.

Applied as a featheredge expect to gain up to 30 m² depending on texture of substrate.

Shelf Life:

6 months in dry conditions.

Pot Life:

Approximately 20 minutes at 20 degrees centigrade, this will vary depending on fluctuations in temperatures.

Safety Directions

Hazardous according to the criteria of NOHSC, contain cement silica. Wear gloves and mask when handling. Wash hands thoroughly after use. Material safety data sheets are available upon request.

Manual handling:

Manual handling of this bag without due care and attention may result in personal injury.

Note: Robert Fine Patch 35 is for internal use only. Don't use in wet areas or external areas.

Do not install Fine Patch onto substrates of ambient temperature below 10 degrees.

Do not overwater.

Issued: March 2008

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risks and liability resulting from the use of this product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Roberts Australia ACN 004 709 915
a division of RLA Polymers Pty Ltd
215 Colchester Road, Kilsyth, Victoria 3137, Australia
Tel: (03) 9728 1605 Fax: (03) 9728 6009



Roberts New Zealand
67 Dalgety Drive (P.O. Box 97-575)
Manukau City, Auckland, New Zealand
Tel: (9) 268 0301 Fax: (9) 268 0305

adhesives
levelling powders
hot melt tapes