



TECHNICAL DATA SHEET

Customer Services
CHC : 03 379 7067 or AKL: 09 443 7067
Email: help@giltedge.co.nz

Technical & Sales Assistance
Email: help@giltedge.co.nz
www.giltedge.co.nz

Gilt Edge Industries Ltd

UNIVERSAL PRIMER

Rapid Drying Acrylic Primer

Characteristics

- Rapid drying, solvent-free, low VOC water-based acrylic primer.
- Formulated to assist adhesive and waterproofing bonding on difficult and problematic surfaces.
- Intended for use over porous and non-porous substrates, such as existing tiles, old paint (excepting oil-based paints), vinyl adhesive, vinyl tile, carpet adhesive residue, metal and sealed or burnished concrete floors.
- Compatible with cement-based ceramic tile adhesives.
- Can be applied both internally and externally over clean and dry surfaces.

Preparation

- Ensure surface is clear of oil, grease and wax.
- All loose materials (dust, grit, etc) must be removed prior to application.
- Concrete floors must be dry in accordance with A.S.3958.1-2007.
- Where temperature is outside the range of 5°C – 30°C, contact DGL Bondlast for technical advice.
- Thoroughly mix prior to use.

Application

On Porous Substrates:

- Dilute Universal Primer using 2 parts clean water to 1 part Universal Primer.
- Apply primer using a roller, brush or broom, ensuring the entire area is primed.
- Very absorbent concrete may require a second coat of Universal Primer diluted to match the first coat.
- Allow to cure for 30 minutes (at 20°C).

On Non-Porous Substrates:

- Apply an even layer of undiluted Universal Primer, ensuring the entire area is primed.
- Allow to cure for 2 hours (at 20°C).

Once Universal Primer has dried to a clear, tack-free film, adhesive or waterproofing membranes may be applied to the surface.

Cleanup

Clean all equipment with water after use.



Flexi-SEAL
Licensed waterproofing system

Packaging/Shelf Life

Universal Primer can be stored for up to 12 months in a sealed container. It should be stored in a dry area, above ground, out of direct sunlight. Available in 1L, 5L, and 20L.

Coverage

Universal Primer will cover approximately 8m² per litre of product either undiluted or after dilution.

Notes

A Material Safety Data Sheet is available upon request.

- Do not apply on substrates subject to rising damp.
- Do not apply at a thickness greater than 1mm.
- Do not apply on tiles with wax or excessive gloss coating.