AUGUST 2025

YOUR FLOOR. OUR PROMISE.

UZIN PRODUCT CATALOGUE

GILT EDGE INDUSTRIES

Every Flooring Installation Deserves the **“GILT EDGE”** Finish

WELCOME TO THE UZIN PRODUCT CATALOGUE

NEW ZEALAND EDITION - 2025

This catalogue presents the core range of UZIN professional substrate preparation and flooring installation products available in New Zealand.

Each product is part of a fully integrated system, engineered for performance, long-term reliability, and environmental responsibility, trusted by flooring professionals around the world.

Designed with our industries professionals in mind, this catalogue is a practical, easy-to-navigate resource.

Simply click any product image in the catalogue to access the most recent technical data sheet.

All products listed in this catalogue are distributed exclusively in New Zealand by Gilt Edge Industries. For availability, pricing, or ordering support, please contact your local Gilt Edge representative.

If you require system recommendations, specification guidance, or detailed technical support, our team is here to assist. The UZIN Technical Support Team and Gilt Edge Industries are committed to making specification and installation as straightforward and reliable as possible.

Whether you're specifying, selling, or installing UZIN products, we're here to help ensure every project is delivered with clarity and confidence.

PRIMERS











UZIN PE260	UZIN PE280	UZIN PE414 BiTurbo	UZIN PE460	UZIN PE650
Standard everyday primer for concrete, cementitious, and some timber surfaces. Most commonly used 3:1 (water to primer ratio) for priming concrete & cementitious substrates.	Rapid drying primer for substrates with any level of porosity. Most commonly used for priming low porosity substrates before levelling compound application.	One component, fast drying moisture barrier & primer, can be used on substrates with up to **95% RH**. Most commonly used on ‘green’ slabs. Two coat application before installation of moisture sensitive floor coverings.	Two component epoxy moisture barrier & primer for most substrates, with up to **98% RH**. Can be combined with silica sand as an epoxy filler. Most commonly used as a moisture barrier & primer on high RH concrete.	Flexible cementitious primer for jointed surfaces prior to levelling compound applications. Most commonly used for priming T&G plank, or tiled surfaces prior to levelling compound application.

LEVELLING / REPAIR / RAMPING / SKIM COAT COMPOUNDS











UZIN NC157 SP Levelling Compound	UZIN NC164 SP Levelling Compound	UZIN NC168 SP Levelling Compound	UZIN NC181 Repair / Ramping Compound	UZIN NC888 S Skim Coat
Application Thickness: 3–50 mm **Suitable Substrates:** Concrete, cementitious screeds, composite timber sheets (e.g. particle board), jointed timber subfloors (e.g. tongue & groove) **Suitable Floor Coverings:** Resilient flooring, textile, vinyl, LVT, ceramic tile, engineered timber **Ready for Flooring:** After 24 hours at 3 mm in suitable conditions	**Application Thickness:** 1-10 mm **Suitable Substrates:** Concrete, cementitious screeds/boards. **Suitable Floor Coverings:** Resilient flooring, textile, vinyl, LVT, ceramic tile, engineered timber **Ready for Flooring:** After 24 hours at 3 mm in suitable conditions	**Application Thickness:** 1-25 mm **Suitable Substrates:** Concrete, cementitious screeds, composite timber sheets (e.g. particle board), jointed timber subfloors (e.g. tongue & groove) **Suitable Floor Coverings:** Resilient flooring, textile, vinyl, LVT, ceramic tile, engineered timber, solid timber. **Ready for Flooring:** After 24 hours at 3 mm in suitable conditions	**Application Thickness:** 1-100mm **Suitable Substrates:** Concrete, cementitious screeds, composite timber sheets (e.g. particle board), jointed timber subfloors (e.g. tongue & groove) **Suitable Floor Coverings:** Resilient flooring, textile, vinyl, LVT, ceramic tile, engineered timber, solid timber. **Ready for Flooring:** After 45 minutes at 3 mm in suitable conditions	**Application Thickness:** 1-4mm **Suitable Substrates:** Concrete, cementitious screeds, composite timber sheets (e.g. particle board), jointed timber subfloors (e.g. tongue & groove) **Suitable Floor Coverings:** Resilient flooring, textile, vinyl, LVT, ceramic tile, engineered timber, solid timber. **Ready for Flooring:** After 15 minutes at 3 mm in suitable conditions

LEVELLING COMPOUNDS – INDENT ONLY AVAILABLE FOR PROJECTS





UZIN NC160 Levelling Compound	UZIN NC170 Levelling Compound
Application Thickness: 0-20mm **Suitable Substrates:** Concrete, cementitious screeds, composite timber sheets (e.g. particle board). **Suitable Floor Coverings:** Resilient flooring, textile, vinyl, LVT, ceramic tile, engineered timber, solid timber. **Ready for Flooring:** After 20 hours at 3 mm in suitable conditions.	**Application Thickness:** 1mm – No Limitation in application thickness **Suitable Substrates:** Concrete, cementitious screeds, composite timber sheets (e.g. particle board). **Suitable Floor Coverings:** Resilient flooring, textile, vinyl, LVT, ceramic tile, engineered timber, solid timber. **Ready for Flooring:** Many types of floor covering can be installed after just 6 hours. (at 5mm in suitable conditions)

SINCE THE INTRODUCTION OF THE UZIN SP LEVELLERS RANGE IN 2025, OUR LEGACY LEVELLERS UZIN NC160 & NC170 ARE NOW ONLY AVAILABLE AS INDENT ORDERS FOR PROJECTS.

UZIN ALSO MANUFACTURE A WHOLE RANGE OF INNOVATIVE PRODUCTS WHICH CAN BE ORDERED FOR SPECIFIC PROJECTS, WITH A SHIPPING TIME OF APPROXIMATELY 16 WEEKS.

FOR MORE INFORMATION ON OUR INDENT PRODUCTS, PLEASE CONTACT GILT EDGE INDUSTRIES.

ADHESIVES















KE 2000 S	KE 2000 SL	KE66	KE 68 T	UZ 57	KR 430	MK 95
Dispersion adhesive for Resilient, Textile & Wall **Coverings:** PVC/CV, rubber (≤4 mm), textile, LVT/design floors, linoleum (≤3.2 mm), wall coverings. **Substrates:** Absorbent, levelled, non-absorbent (PVC/CV/rubber only, double-drop) **Notes:**UFH Compatible, castor chairs, RAL 991 A2 cleaning, heavy wear areas	**Conductive adhesive for Resilient & Textile** **Coverings:** Conductive PVC, rubber (≤3 mm), linoleum (≤4 mm), textile **Substrates:** Absorbent, levelled; limited use on dense/non-absorbent **Notes:** UFH compatible, castor chairs, RAL 991 A2 cleaning, heavy wear areas	**Dispersion adhesive for Resilient & Healthcare Flooring** **Coverings:** LVT, PVC/CV (tiles/sheets), rubber (≤4 mm), textile (healthcare) **Substrates:** Absorbent, levelled **Notes:** UFH compatible, castor chairs, RAL 991 A2 cleaning, high-temp & industrial areas	**Hybrid adhesive for Floors & Walls** **Coverings:** LVT, wall cladding (PVC/hard plastic), rubber tiles, granulated rubber ≤8 mm **Substrates:** Absorbent/non-absorbent, elastic/deformable (e.g. underlays, wood,) **Notes:** UFH compatible, EXTENDED APPLICATIONS: wooden wall cladding, engineered wood flooring on the wall	**Dispersion adhesive for Textile Flooring** **Coverings:** Textile (all backings incl. latex/wool/felt), woven, stiff types, PVC/CV with fleece backing **Substrates:** Absorbent, levelled, UZIN underlays **Notes:** UFH compatible, castor chairs, RAL 991 A2 cleaning, normal commercial use.	**Heavy-duty PU adhesive** **Coverings:** LVT, PVC/CV (tiles), rubber (≤10 mm), linoleum (tiles ≤4 mm), astroturf **Substrates:** Absorbent/non-absorbent, resilient/deformable **Notes:** UFH compatible, castor chairs, RAL 991 A2 cleaning, very high loads in commercial and industrial environments.	**Hard-elastic adhesive for T&G Wood Flooring** **Coverings:** Solid wood, strip parquet **Substrates:** Cementitious/anhydrite screeds, concrete, P4–P7, OSB2–OSB4 (screwed), precast boards, suitable compounds, UZIN underlays **Notes:** UFH compatible, EXTENDED APPLICATIONS: engineered wood flooring, engineered wooden planks.

MEMBRANES / UNDERLAY / DRY ADHESIVE









UZIN RR185	UZIN RR201	UZIN RR203	UZIN SIGAN ELEMENTS
Stabilising, Damp-Proofing Underlay (loose-laid) **Use:** Moisture barrier (up to 98% RH/5 CM-%), isolating layer over oily/suboptimal substrates **Substrates:** Most solid, level surfaces incl. old floors (PVC, linoleum, wood, tile), coated or moist substrates **Notes:** Removable, suitable under resilient/textile floors, balconies, terraces; supports castor chair use & wet cleaning	**Reinforcing Fleece for Levelling Compounds** **Use:** Substrate stabilisation, compound reinforcement, UZIN Turbolight® & RR 201 systems **Substrates:** All screeds, concrete, adhesive/compound residues, chipboard (P4–P7), OSB2–OSB4, precast screeds, raised floors, underlays **Notes:** Ideal for transitions, UFH, and all residential/commercial/industrial settings	**Crack-bridging Fleece for Substrate Movement & Repair** **Use:** Reinforces cracks/day joints (≤5 mm) and transitions across changing substrates **Substrates:** All screeds, concrete, adhesive residues, P4–P7, OSB2–OSB4, precast boards, raised floors, underlays **Notes:** Ideal for UFH, repairs, and all residential/commercial/industrial use	**Dry Adhesive for PVC, Flotex & Dust Mats** **Coverings:** LVT (≤3.2 mm), PVC tiles/sheets, Flotex, PVC-backed dust mats **Substrates:** PVC, CV, linoleum (treated), rubber, PO, epoxy/PUR (≥3 mo), terrazzo, artificial stone **Notes:** UFH compatible, RAL 991 A2 cleaning, heavy commercial/industrial use

UZIN COMPONENTS











UZIN KR 516	UZIN Foam Expansion Strip	UZIN Level Pins	UZIN Reinforcement Fibres	Silica Sand
Crack Repair & Bonding Resin **Use:** Fills cracks/joints, bonds rails/profiles, repairs concrete/stone, installs stair angles **Substrates:** Cement/calcium sulphate screeds, concrete, magnesia/xylolite, tile, stone, terrazzo **Notes:** residential & commercial use	**Self-adhesive PE Expansion Strip (5 mm x 50 mm)** **Use:** Separates floor from wall before applying levelling compounds to allow movement and prevent cracking **Notes:** Also acts as an acoustic insulation layer, minimising nose transfer.	**Self-adhesive Depth Gauge for Levelling Compounds** **Use:** Accurate measurement of levelling layers and screeds up to 100 mm depth	**Alkali-resistant Glass Fibres for Levelling Compounds** **Use:** Reinforces weak substrates, reduces cracking, improves structural strength during refurbishment **Notes:** If a levelling compound application is to be left uncovered for an extended period, reinforcement fibres can prevent surface cracking.	**Fire-Dried Silica Sand (0.3–0.8 mm)** **Use:** Sprinkling/filling with primers (e.g. PE 460/414 BiTurbo) & repair resins (e.g. KR 516) **Function:** Improves dried surface adhesion, adjusts consistency; suitable for interior/exterior use. **Notes:** Can also be used as a bulk fill aggregate for levelling compounds.

CONTACT US FOR PROJECT SUPPORT

GILT EDGE INDUSTRIES

Whether you're developing specifications, planning an installation, or navigating site challenges, our team is here to help.

The technical support team at Gilt Edge Industries offer trusted, project-specific advice backed by decades of technical expertise. From system recommendations to compliance and performance guidance, we’re committed to making your flooring projects smoother, safer, and more successful.

Get in touch — we’re ready to support you at every stage.

PHONE: 0800 445 833

EMAIL: HELP@GILTEDGE.CO.NZ